

# FINAL REPORT



## GERDAU MACSTEEL, INC

MONROE, MICHIGAN

**MONROE MILL:  
STACK TEST REPORT - ELECTRIC ARC FURNACE (EAF) AND  
LADLE METALLURGY SYSTEM (LMF)**

RWDI #2300259

January 27, 2023

### SUBMITTED TO

**Christopher Hessler**  
**Gerdau MacSteel, Inc**  
Regional Environmental Manager  
Christopher.Hessler@gerdau.com

**Gerdau MacSteel, Inc**  
**Monroe Mill**  
3000 East Front Street  
Monroe, Michigan 48161  
T: 734.384.6544

**Scott Miller**  
**EGLE, Air Quality Division**  
301 East Louis Glick Highway  
Jackson, Michigan 49201

**TPU Supervisor**  
**EGLE, Air Quality Division**  
Constitution Hall, 2<sup>nd</sup> Floor South  
525 West Allegan Street  
Lansing, Michigan 48933

### SUBMITTED BY

**Brad Bergeron, A.Sc.T., d.E.T.**  
Senior Project Manager | Principal  
Brad.Bergeron@rwdi.com | ext. 2428

**Steve Smith, QSTI**  
Project Manager  
Steve.Smith@rwdi.com | ext. 3703

**RWDI USA LLC**  
**Consulting Engineers & Scientists**  
2239 Star Court  
Rochester Hills, Michigan 48309

T: 248.841.8442  
F: 519.823.1316



rwdi.com

This document is intended for the sole use of the party to whom it is addressed and may contain information that is privileged and/or confidential. If you have received this in error, please notify us immediately. Accessible document formats provided upon request. © RWDI name and logo are registered trademarks in Canada and the United States of America.

# FINAL REPORT



## GERDAU MACSTEEL, INC

MONROE, MICHIGAN

**MONROE MILL:  
STACK TEST REPORT - ELECTRIC ARC FURNACE (EAF) AND  
LADLE METALLURGY SYSTEM (LMF)**

RWDI #2300259

January 27, 2023

### SUBMITTED TO

**Christopher Hessler**  
**Gerdau MacSteel, Inc**  
Regional Environmental Manager  
Christopher.Hessler@gerdau.com

**Gerdau MacSteel, Inc**  
**Monroe Mill**  
3000 East Front Street  
Monroe, Michigan 48161  
T: 734.384.6544

**Scott Miller**  
**EGLE, Air Quality Division**  
301 East Louis Glick Highway  
Jackson, Michigan 49201

**TPU Supervisor**  
**EGLE, Air Quality Division**  
Constitution Hall, 2<sup>nd</sup> Floor South  
525 West Allegan Street  
Lansing, Michigan 48933

### SUBMITTED BY

**Brad Bergeron, A.Sc.T., d.E.T.**  
Senior Project Manager | Principal  
Brad.Bergeron@rwdi.com | ext. 2428

**Steve Smith, QSTI**  
Project Manager  
Steve.Smith@rwdi.com | ext. 3703

**RWDI USA LLC**  
**Consulting Engineers & Scientists**  
2239 Star Court  
Rochester Hills, Michigan 48309

T: 248.841.8442  
F: 519.823.1316



rwdi.com

This document is intended for the sole use of the party to whom it is addressed and may contain information that is privileged and/or confidential. If you have received this in error, please notify us immediately. Accessible document formats provided upon request. © RWDI name and logo are registered trademarks in Canada and the United States of America.



## EXECUTIVE SUMMARY

RWDI USA LLC (RWDI) has been retained by Gerdau MacSteel, Inc (Gerdau) to complete the emission sampling program at the Gerdau Monroe Mill located at 3000 East Front Street, Monroe, Michigan. The testing evaluated PM, PM2.5, PM10, and Visual Emissions from the EAF and LMF. The test program was completed the week of November 28<sup>th</sup>, 2022.

**Executive Table i:** Average – ROP Limits for FGMELTSHOP - EAF, LMF, and VTD

| Parameter            | Concentration                |                            |
|----------------------|------------------------------|----------------------------|
|                      | Test Average                 | Permit Limit               |
| PM2.5                | 5.06 lb/hr                   | 10.9 lb/hr                 |
| PM2.5                | 0.037 lb/ton of liquid steel | 0.1 lb/ton of liquid steel |
| PM10                 | 7.29 lb/hr                   | 10.9 lb/hr                 |
| PM (Filterable Only) | 0.0014 Grains/dscf           | 0.0018 Grains/dscf         |
| PM (Filterable Only) | 3.24 lb/hr                   | 7.2 lb/hr                  |

**Executive Table ii:** Average – PTI Limits for – EUEAF - EAF Baghouse

| Parameter                            | Concentration      |                    |
|--------------------------------------|--------------------|--------------------|
|                                      | Test Average       | Permit Limit       |
| PM2.5                                | 2.45 lb/hr         | 12.91 lb/hr        |
| PM10                                 | 2.60 lb/hr         | 12.91 lb/hr        |
| PM (Filterable Only)                 | 0.0004 Grains/dscf | 0.0018 Grains/dscf |
| PM (Filterable Only)                 | 0.63 lb/hr         | 7.84 lb/hr         |
| Visual Emissions from Baghouse Stack | 0% Opacity         | 3% Opacity         |
| Visual Emissions from vents/openings | 0% Opacity         | 6% Opacity         |

# FINAL REPORT



## GERDAU MACSTEEL, INC

MONROE, MICHIGAN

**MONROE MILL:  
STACK TEST REPORT - ELECTRIC ARC FURNACE (EAF) AND  
LADLE METALLURGY SYSTEM (LMF)**

RWDI #2300259

January 27, 2023

### SUBMITTED TO

**Christopher Hessler**  
**Gerdau MacSteel, Inc**  
Regional Environmental Manager  
Christopher.Hessler@gerdau.com

**Gerdau MacSteel, Inc**  
**Monroe Mill**  
3000 East Front Street  
Monroe, Michigan 48161  
T: 734.384.6544

**Scott Miller**  
**EGLE, Air Quality Division**  
301 East Louis Glick Highway  
Jackson, Michigan 49201

**TPU Supervisor**  
**EGLE, Air Quality Division**  
Constitution Hall, 2<sup>nd</sup> Floor South  
525 West Allegan Street  
Lansing, Michigan 48933

### SUBMITTED BY

**Brad Bergeron, A.Sc.T., d.E.T.**  
Senior Project Manager | Principal  
Brad.Bergeron@rwdi.com | ext. 2428

**Steve Smith, QSTI**  
Project Manager  
Steve.Smith@rwdi.com | ext. 3703

**RWDI USA LLC**  
**Consulting Engineers & Scientists**  
2239 Star Court  
Rochester Hills, Michigan 48309

T: 248.841.8442  
F: 519.823.1316



rwdi.com

This document is intended for the sole use of the party to whom it is addressed and may contain information that is privileged and/or confidential. If you have received this in error, please notify us immediately. Accessible document formats provided upon request. © RWDI name and logo are registered trademarks in Canada and the United States of America.



## EXECUTIVE SUMMARY

RWDI USA LLC (RWDI) has been retained by Gerdau MacSteel, Inc (Gerdau) to complete the emission sampling program at the Gerdau Monroe Mill located at 3000 East Front Street, Monroe, Michigan. The testing evaluated PM, PM2.5, PM10, and Visual Emissions from the EAF and LMF. The test program was completed the week of November 28<sup>th</sup>, 2022.

**Executive Table i:** Average – ROP Limits for FGMELTSHOP - EAF, LMF, and VTD

| Parameter            | Concentration                |                            |
|----------------------|------------------------------|----------------------------|
|                      | Test Average                 | Permit Limit               |
| PM2.5                | 5.06 lb/hr                   | 10.9 lb/hr                 |
| PM2.5                | 0.037 lb/ton of liquid steel | 0.1 lb/ton of liquid steel |
| PM10                 | 7.29 lb/hr                   | 10.9 lb/hr                 |
| PM (Filterable Only) | 0.0014 Grains/dscf           | 0.0018 Grains/dscf         |
| PM (Filterable Only) | 3.24 lb/hr                   | 7.2 lb/hr                  |

**Executive Table ii:** Average – PTI Limits for – EUEAF - EAF Baghouse

| Parameter                            | Concentration      |                    |
|--------------------------------------|--------------------|--------------------|
|                                      | Test Average       | Permit Limit       |
| PM2.5                                | 2.45 lb/hr         | 12.91 lb/hr        |
| PM10                                 | 2.60 lb/hr         | 12.91 lb/hr        |
| PM (Filterable Only)                 | 0.0004 Grains/dscf | 0.0018 Grains/dscf |
| PM (Filterable Only)                 | 0.63 lb/hr         | 7.84 lb/hr         |
| Visual Emissions from Baghouse Stack | 0% Opacity         | 3% Opacity         |
| Visual Emissions from vents/openings | 0% Opacity         | 6% Opacity         |



**Executive Table iii: Average – PTI Limits for – FGLMFVTD – LMF Baghouse**

| Parameter            | Concentration      |                    |
|----------------------|--------------------|--------------------|
|                      | Test Average       | Permit Limit       |
| PM2.5                | 2.61 lb/hr         | 8.95 lb/hr         |
| PM10                 | 4.69 lb/hr         | 8.95 lb/hr         |
| PM (Filterable Only) | 0.0010 Grains/dscf | 0.0018 Grains/dscf |
| PM (Filterable Only) | 2.61 lb/hr         | 3.88 lb/hr         |

**Executive Table iv: Average – ROP Limits for – EUEAF – EAF Baghouse**

| Parameter                                  | Concentration      |                    |
|--|--------------------|--------------------|
|  | Test Average       | Permit Limit       |
| PM (Filterable Only)                       | 0.0004 Grains/dscf | 0.0052 Grains/dscf |
| Visual Emissions from Baghouse Stack       | 0% Opacity         | 3% Opacity         |
| Visual Emissions from Vents and Openings   | 0% Opacity         | 0% Opacity         |
| Visible Emissions from EUEAF Shop Building | 0% Opacity         | 6% Opacity         |

**Executive Table v: Average – ROP Limits for – EULMF – LMF Baghouse**

| Parameter                            | Concentration |              |
|--------------------------------------|---------------|--------------|
|                                      | Test Average  | Permit Limit |
| Visual Emissions from Baghouse Stack | 0% Opacity    | 5% Opacity   |



# TABLE OF CONTENTS

|          |   |          |
|----------|---|----------|
| <b>1</b> | <b>INTRODUCTION .....</b>   | <b>1</b> |
| 1.1      | Location and Dates of Testing.....  | 1        |
| 1.2      | Purpose of Testing.....   | 1        |
| 1.3      | Description of Source .....   | 1        |
| 1.4      | Personnel Involved in Testing .....   | 2        |
| <b>2</b> | <b>SUMMARY OF RESULTS.....</b>  | <b>3</b> |
| 2.1      | Operating Data.....   | 3        |
| 2.2      | Applicable Permit Number .....  | 3        |
| <b>3</b> | <b>SOURCE DESCRIPTION .....</b>   | <b>3</b> |
| 3.1      | Description of Process and Emission Control Equipment.....                                  | 3        |
| 3.2      | Process Flow Sheet or Diagram (if applicable).....  | 3        |
| 3.3      | Type and Quantity of Raw and Finished Materials.....  | 3        |
| 3.4      | Normal Rated Capacity of Process.....   | 3        |
| 3.5      | Process Instrumentation Monitored During the Test.....                                      | 4        |
| <b>4</b> | <b>SAMPLING AND ANALYTICAL PROCEDURES .....</b>   | <b>4</b> |
| 4.1      | Description of Sampling Train and Field Procedures.....                                     | 4        |
| 4.1.1    | Stack Velocity, Temperature, and Volumetric Flow Rate Determination (USEPA Method 1-4)..... | 4        |
| 4.1.2    | Sampling for PM/PM2.5/PM10/CPM (USEPA Method 201A/202) .....                                | 5        |
| 4.2      | Description of Recovery and Analytical Procedures .....                                     | 5        |
| 4.3      | Sampling Port Description.....  | 5        |
| <b>5</b> | <b>TEST RESULTS AND DISCUSSION .....</b>  | <b>6</b> |
| 5.1      | Detailed Results.....   | 6        |
| 5.2      | Discussion of Results.....  | 7        |



# 1 INTRODUCTION

RWDI USA LLC (RWDI) has been retained by Gerdau MacSteel, Inc (Gerdau) to complete the emission sampling program at the Gerdau Monroe Mill located at 3000 East Front Street, Monroe, Michigan. The testing evaluated PM, PM<sub>10</sub>, PM<sub>2.5</sub>, and Visual Emissions from the Electric Arc Furnace (EAF) and Ladle Metallurgic Furnace (LMF).

## 1.1 Location and Dates of Testing

The test program was completed at the Gerdau Monroe Mill the week of November 28<sup>th</sup>, 2022.

## 1.2 Purpose of Testing

The purpose of this test program was conducted per PTI 75-18 and MI-ROP-B7061-2016.

## 1.3 Description of Source

Gerdau Monroe Mill is a producer of Special Bar Quality (SBQ) steel. The steel-melting process utilizes Electric Arc Furnace Technology (EAF). The EAF is a refractory-lined cylindrical vessel made of steel plates and having a bowl-shaped hearth and a dome-shaped roof. Water-cooled panels are used for the shell and roof to improve refractory efficiency. Three electrodes, powered by a transformer, are mounted on a superstructure above the furnace and are lowered and raised through ports in the furnace roof. The electrode conveys the energy for melting the scrap steel. Supplemental energy is provided by an oxy-fuel burner and an oxygen/coke lance which swings into the slag door area and operates during the melting/refining process. The furnace is mounted on curved rockers, which allow tilting for slagging and bottom tapping. The EAF melts scrap metal in a batch operation referred to as a heat.

The LMF is a complete ladle metallurgy system which includes arc reheating, alloy additions, powder injections and stirring.





## 2 SUMMARY OF RESULTS

### 2.1 Operating Data

Gerdaul personnel made sure the process was operating correctly and production was at acceptable capacity.

### 2.2 Applicable Permit Number

MI-ROP-B7061-2016 and PTI 75-18.

## 3 SOURCE DESCRIPTION

### 3.1 Description of Process and Emission Control Equipment

Emissions from the processes within the Melt Shop are directed to two baghouses (DVBAGHOUSE-01 and DVLMFBAGHOUSE). DVBAGHOUSE-01 serves EUEAF and also accepts emissions captured by the canopy hood in the Melt Shop. DVBAGHOUSE-01 is a positive pressure baghouse with reverse air cleaning. Three main exhaust fans and one direct evacuation control (DEC) fan. The baghouse is equipped with two exhaust stacks, SVBH-01-STACK1 and SVBH-01-STACK2. CO is combusted in the DEC combustion chamber. Screw conveyors transfer the collected baghouse dust to a pneumatic conveying system which transfers the dust into a silo for storage until removed from the site. The second baghouse (DVLMFBAGHOUSE) serves the LMF and VTD operations in the Melt Shop. DVLMFBAGHOUSE is a positive pressure baghouse with reverse air cleaning and is equipped with a single exhaust stack. Dust collected by DVLMFBAGHOUSE is stored in the baghouse hoppers until it is removed from the site.

Fugitive emissions from within the Melt Shop that reach the roof top monitors are captured and directed to the LMF Baghouse.

### 3.2 Process Flow Sheet or Diagram (if applicable)

A process flow diagram can be sent upon request.

### 3.3 Type and Quantity of Raw and Finished Materials

Scrap steel is charged per heat into the EAF. During the heat, additives, alloys, and fluxes are added.

### 3.4 Rated Capacity of Process

Maximum rated capacity is 130 tons of liquid steel produced per heat.



### 3.5 Process Instrumentation Monitored During the Test

Operators regulate the process and control production rates.

- Cast Rate (tons/hr)
- Tap Amounts (tons)

## 4 SAMPLING AND ANALYTICAL PROCEDURES

### 4.1 Description of Sampling Train and Field Procedures

The emission test program will utilize the following test methods codified at Title 40, Part 60, Appendix A of the Code of Federal Regulations (40 CFR 60, Appendix A):

- Method 1 – Sample and Velocity Traverses for Stationary Sources
- Method 2 – Determination of Stack Gas Velocity and Volumetric Flowrate
- Method 3 – Determination of Molecular Weight of Dry Stack Gases (by Fyrite)
- Method 4 – Determination of Moisture Content in Stack Gases
- Method 201A – Determination of PM/PM2.5/PM10 from Stationary Sources
- Method 202 – Determination of Condensable Particulate Matter from Stationary Sources
- Method 9 – Visual Emissions from Stationary Sources

#### 4.1.1 Stack Velocity, Temperature, and Volumetric Flow Rate Determination (USEPA Method 1-4)

Traverse points and determination of upstream and downstream distances from flow disturbance were determined using U.S. EPA Method 1.

The exhaust velocities and flow rates were determined following U.S. EPA Method 2, "Determination of Stack Gas Velocity and Volumetric Flow Rate (Type S Pitot Tube)". Velocity measurements were taken with a pre-calibrated S-Type pitot tube and incline manometer or digital manometer. Volumetric flow rates were determined following the equal area method as outlined in U.S. EPA Method 2. Temperature measurements were made simultaneously with the velocity measurements and were conducted using a chromel-alumel type "k" thermocouple in conjunction with a calibrated digital temperature indicator.

The dry molecular weight of the stack gas was determined following calculations outlined in U.S. EPA Method 3, using a fyrite.

Stack moisture content was determined through direct condensation and according to U.S. EPA Method 4, "Determination of Moisture Content of Stack Gases". Method 4 was conducted through the 201A/202 train.



#### 4.1.2 Sampling for PM/PM<sub>10</sub>/PM<sub>2.5</sub>/CPM (USEPA Method 201A/202)

Three (3) 240-minute tests were performed on SVBH-01-Stack-01 (EAF West (Red)), SVBH-01-Stack-02 (EAF East (White)) and SVBHLMF-Stack (LMF). All tests were completed simultaneously. RWDI's USEPA Method 201A/202 sampling train consists of (1) a stainless steel nozzle, (2) a stainless steel PM<sub>10</sub> cyclone head, (3) a stainless steel PM<sub>2.5</sub> cyclone head, (4) an in stack filter housing, (5) a borosilicate glass probe or liner, (6) a vertical condenser, (7) an empty pot-bellied impinger, (8) an empty modified Greenburg-Smith (GS) impinger, (9) Teflon filter, (10) a second modified GS impinger with 100 ml of water and a third impinger containing silica gel, (11) a sample line and meter box. USEPA Method 201A collects the filterable fractions of PM/PM<sub>10</sub>/PM<sub>2.5</sub> and USEPA Method 202 collects the condensable fraction of PM<sub>10</sub> and PM<sub>2.5</sub>.

A sampling train leak check was conducted before and after each test. After completion of each test, the filter was recovered, the nozzle, PM<sub>10</sub>, and PM<sub>2.5</sub> head were recovered into clean sample jars following USEPA Method 201A. The impinger train was purged with nitrogen for one hour at a flowrate of 14 liters per minute. After the purge, all the glassware was recovered per USEPA Method 202.

### 4.2 Description of Recovery and Analytical Procedures

The samples were all recovered following USEPA Method 201A and 202.

### 4.3 Sampling Port Description

The sampling locations are all outside.

**Table 4.3:** Summary of Exhaust Parameters

| Source  | Diameter (in.) | Approximate Duct Diameters from Flow Disturbance | Number of Ports | Points per Traverse | Total Points per Test |
|---|----------------|--|-----------------|---------------------|-----------------------|
| SVBH-01-Stack-01<br>EUEAF Baghouse<br>Stack 1<br>(EAF West (Red))   | 135            | ~2.6 downstream<br>and 2.7 upstream              | 4               | 12                  | 24                    |
| SVBH-01-Stack-02<br>EUEAF Baghouse<br>Stack 2<br>(EAF East (White)) | 135.5          | ~2.6 downstream<br>and ~2.7 upstream             | 4               | 12                  | 24                    |
| SVBHLMF-Stack<br>LMF Baghouse<br>(LMF)                              | 110            | >8 downstream<br>and >2 upstream                 | 4               | 6                   | 12                    |



## 5 TEST RESULTS AND DISCUSSION

### 5.1 Detailed Results

**Table 5.1:** Average – ROP Limits for FGMELTSHOP - EAF, LMF, and VTD

| Parameter            | Concentration                |                            |
|----------------------|------------------------------|----------------------------|
|                      | Test Average                 | Permit Limit               |
| PM2.5                | 5.06 lb/hr                   | 10.9 lb/hr                 |
| PM2.5                | 0.037 lb/ton of liquid steel | 0.1 lb/ton of liquid steel |
| PM10                 | 7.29 lb/hr                   | 10.9 lb/hr                 |
| PM (Filterable Only) | 0.0014 Grains/dscf           | 0.0018 Grains/dscf         |
| PM (Filterable Only) | 3.24 lb/hr                   | 7.2 lb/hr                  |

**Table 5.2:** Average – PTI Limits for – EUEAF - EAF Baghouse

| Parameter                            | Concentration      |                    |
|--------------------------------------|--------------------|--------------------|
|                                      | Test Average       | Permit Limit       |
| PM2.5                                | 2.45 lb/hr         | 12.91 lb/hr        |
| PM10                                 | 2.60 lb/hr         | 12.91 lb/hr        |
| PM (Filterable Only)                 | 0.0004 Grains/dscf | 0.0018 Grains/dscf |
| PM (Filterable Only)                 | 0.63 lb/hr         | 7.84 lb/hr         |
| Visual Emissions from Baghouse Stack | 0% Opacity         | 3% Opacity         |
| Visual Emissions from vents/openings | 0% Opacity         | 6% Opacity         |

**RECEIVED**  
FEB 07 2023  
AIR QUALITY DIVISION



**Table 5.3:** Average – PTI Limits for – FGLMFVTD – LMF Baghouse

| Parameter            | Concentration      |                    |
|----------------------|--------------------|--------------------|
|                      | Test Average       | Permit Limit       |
| PM2.5                | 2.61 lb/hr         | 8.95 lb/hr         |
| PM10                 | 4.69 lb/hr         | 8.95 lb/hr         |
| PM (Filterable Only) | 0.0010 Grains/dscf | 0.0018 Grains/dscf |
| PM (Filterable Only) | 2.61 lb/hr         | 3.88 lb/hr         |

**Table 5.4:** Average – ROP Limits for – EUEAF – EAF Baghouse

| Parameter                                  | Concentration      |                    |
|--|--------------------|--------------------|
|  | Test Average       | Permit Limit       |
| PM (Filterable Only)                       | 0.0004 Grains/dscf | 0.0052 Grains/dscf |
| Visual Emissions from Baghouse Stack       | 0% Opacity         | 3% Opacity         |
| Visual Emissions from Vents and Openings   | 0% Opacity         | 0% Opacity         |
| Visible Emissions from EUEAF Shop Building | 0% Opacity         | 6% Opacity         |

**Table 5.5:** Average – ROP Limits for – EULMF – LMF Baghouse

| Parameter                            | Concentration |              |
|--------------------------------------|---------------|--------------|
|                                      | Test Average  | Permit Limit |
| Visual Emissions from Baghouse Stack | 0% Opacity    | 5% Opacity   |

## 5.2 Discussion of Results

The detailed results can be found in **Appendices B, C, D,** and **E.** Note, the laboratory detected visible solid residue in LMF T1 <10 to >2.5 fraction of the acetone rinse from USEPA Method 201A. The data was used as is for the report. We believe this was an unrelated to the process emissions.

## 5.3 Variations in Testing Procedures

There were not testing variations.



## 5.4 Process Upset Conditions During Testing

There were no process upsets.

## 5.5 Maintenance Performed in Last Three Months

There has been no significant maintenance on the EAF or LMF in the last three months. Normal routine maintenance is completed as scheduled.

## 5.6 Re-Test

This was not a retest.

## 5.7 Audit Samples

This test did not require any audit samples.

## 5.8 Field Data Sheets

Field data sheets can be found in **Appendices B, C, D, and E.**

## 5.9 Calibration Sheets

Calibration sheets can be found in **Appendix F.**


## 5.10 Sample Calculations

Sample calculations can be found in **Appendix G.**

## 5.11 Laboratory Data

Laboratory data can be found in **Appendix H.**

# TABLES



**Table 1: Summary of Sampling Parameters and Methodology**

| Source Location                       | No. of Tests per Stack | Sampling Parameter                   | Sampling Method                            |
|---------------------------------------|------------------------|--------------------------------------|--|
| SVBH-01-Stack 2<br>EAF - East (White) | 3                      | Velocity, Temperature and Flow Rate  | U.S. EPA <sup>[1]</sup> Methods 1-4        |
|                                       | 3                      | Total Particulate Matter             | U.S. EPA [1] Method 201A (Filterable Only) |
|                                       | 3                      | PM <sub>10</sub> / PM <sub>2.5</sub> | U.S. EPA [1] Method 201A/202               |
|                                       | 3                      | Oxygen, Carbon Dioxide               | U.S. EPA [1] Method 3                      |
|                                       | 3                      | Visible Emissions                    | U.S. EPA [1] Method 9                      |
| SVBH-01-Stack 1<br>EAF - West (Red)   | 3                      | Velocity, Temperature and Flow Rate  | U.S. EPA <sup>[1]</sup> Methods 1-4        |
|                                       | 3                      | Total Particulate Matter             | U.S. EPA [1] Method 201A (Filterable Only) |
|                                       | 3                      | PM <sub>10</sub> / PM <sub>2.5</sub> | U.S. EPA [1] Method 201A/202               |
|                                       | 3                      | Oxygen, Carbon Dioxide               | U.S. EPA [1] Method 3                      |
|                                       | 3                      | Visible Emissions                    | U.S. EPA [1] Method 9                      |
| SVBHLMF-Stack<br>LMF                  | 3                      | Velocity, Temperature and Flow Rate  | U.S. EPA <sup>[1]</sup> Methods 1-4        |
|                                       | 3                      | Total Particulate Matter             | U.S. EPA [1] Method 201A (Filterable Only) |
|                                       | 3                      | PM <sub>10</sub> / PM <sub>2.5</sub> | U.S. EPA [1] Method 201A/202               |
|                                       | 3                      | Oxygen, Carbon Dioxide               | U.S. EPA [1] Method 3                      |
|                                       | 3                      | Visible Emissions                    | U.S. EPA [1] Method 9                      |

**Notes:**

[1] U.S. EPA - United States Environmental Protection Agency



**Table 2A: Sampling Summary and Sample Log (PM/PM10/PM2.5)**

| Source and Test #   | Sampling Date | Start Time | End Time | Filter ID / Trap ID |
|---|---------------|------------|----------|---------------------|
| <b>SVBH-01-Stack 2 (EAF - East (White)) - Velocity / Total Particulate / PM10 / PM2.5</b> |               |            |          |                     |
| Blank   | 2-Dec-22      | -          | -        | QZ 47-35            |
| Test #1   | 29-Nov-22     | 9:15 AM    | 1:25 PM  | QZ 47-18            |
| Test #2   | 1-Dec-22      | 8:21 AM    | 12:41 PM | QZ 47-36            |
| Test #3   | 2-Dec-22      | 9:15 AM    | 2:12 PM  | QZ 47-33            |
| <b>SVBH-01-Stack 1 (EAF - West (Red)) - Velocity / Total Particulate / PM10 / PM2.5</b>   |               |            |          |                     |
| Blank   | 2-Dec-22      | -          | -        | QZ 47-35            |
| Test #1   | 29-Nov-22     | 9:15 AM    | 1:31 PM  | QZ 47-40            |
| Test #2   | 1-Dec-22      | 8:21 AM    | 12:42 PM | QZ 47-39            |
| Test #3   | 2-Dec-22      | 9:15 AM    | 2:05 PM  | QZ 47-34            |
| <b>SVBHLMF-Stack (LMF) - Velocity / Total Particulate / PM10 / PM2.5</b>                  |               |            |          |                     |
| Blank   | 2-Dec-22      | -          | -        | QZ 47-35            |
| Test #1   | 29-Nov-22     | 9:15 AM    | 1:47 PM  | QZ 47-9             |
| Test #2   | 1-Dec-22      | 8:21 AM    | 1:12 PM  | QZ 47-38            |
| Test #3   | 2-Dec-22      | 9:15 AM    | 2:42 PM  | QZ 47-32            |

**Table 2B: Sampling Summary and Sample Log (Visible Emissions)**

| Source and Test #   | Sampling Date | Start Time | End Time |
|---|---------------|------------|----------|
| <b>SVBH-01-Stack 2 (EAF - East (White)) - Visible Emissions</b> |               |            |          |
| Test #1   | 1-Dec-22      | 8:57 AM    | 9:56 AM  |
| Test #2   | 1-Dec-22      | 9:59 AM    | 10:59 AM |
| Test #3   | 2-Dec-22      | 9:20 AM    | 10:20 AM |
| <b>SVBH-01-Stack 1 (EAF - West (Red)) - Visible Emissions</b>   |               |            |          |
| Test #1   | 1-Dec-22      | 8:58 AM    | 9:57 AM  |
| Test #2   | 1-Dec-22      | 10:00 AM   | 11:00 AM |
| Test #3   | 2-Dec-22      | 9:20 AM    | 10:20 AM |
| <b>SVBHLMF-Stack (LMF) - Visible Emissions</b>                  |               |            |          |
| Test #1   | 1-Dec-22      | 8:57 AM    | 9:56 AM  |
| Test #2   | 1-Dec-22      | 9:59 AM    | 10:59 AM |
| Test #3   | 2-Dec-22      | 9:20 AM    | 10:20 AM |

**Table 3A: Sampling Summary - Flow Characteristics**  
**SVBH-01-Stack 2 (EAF - EAST (White))**

| Stack Gas Parameter                 |      | Test No. 1    | Test No. 2    | Test No. 3    | TOTAL<br>AVERAGE |
|-------------------------------------|------|---------------|---------------|---------------|------------------|
|                                     |      | PM/PM10/PM2.5 | PM/PM10/PM2.5 | PM/PM10/PM2.5 |                  |
| Testing Date                        |      | 29-Nov-22     | 1-Dec-22      | 2-Dec-22      | -                |
| Stack Temperature                   | °F   | 185           | 172           | 176           | 178              |
| Moisture                            | %    | 2.3%          | 1.5%          | 1.4%          | 1.7%             |
| Velocity                            | ft/s | 41.47         | 40.80         | 42.87         | 41.71            |
| Referenced Flow Rate <sup>[3]</sup> | CFM  | 195,425       | 205,455       | 208,171       | 203,017          |
| Sampling Isokinetic Rate            | %    | 103           | 103           | 99            | 102              |

**Notes:**

[1] Referenced flow rate expressed as dry at 101.3 kPa, 68 °F, and Actual Oxygen

**Table 3B: Sampling Summary - Flow Characteristics**  
**SVBH-01-Stack 1 (EAF - West (Red))**

| Stack Gas Parameter                 |      | Test No. 1    | Test No. 2    | Test No. 3    | TOTAL   |
|-------------------------------------|------|---------------|---------------|---------------|---------|
|                                     |      | PM/PM10/PM2.5 | PM/PM10/PM2.5 | PM/PM10/PM2.5 | AVERAGE |
| Testing Date                        |      | 29-Nov-22     | 1-Dec-22      | 2-Dec-22      | -       |
| Stack Temperature                   | °F   | 189           | 174           | 180           | 181     |
| Moisture                            | %    | 2.6%          | 1.3%          | 1.9%          | 1.9%    |
| Velocity                            | ft/s | 37.76         | 36.43         | 37.14         | 37.11   |
| Referenced Flow Rate <sup>[3]</sup> | CFM  | 175,372       | 178,302       | 177,236       | 176,970 |
| Sampling Isokinetic Rate            | %    | 99            | 98            | 97            | 98      |

**Notes:**

[3] Referenced flow rate expressed as dry at 101.3 kPa, 68 °F, and Actual Oxygen

**Table 3C: Sampling Summary - Flow Characteristics**  
**SVBHLMF-Stack (LMF)**

| Stack Gas Parameter                 |      | Test No. 1    | Test No. 2    | Test No. 3    | TOTAL   |
|-------------------------------------|------|---------------|---------------|---------------|---------|
|                                     |      | PM/PM10/PM2.5 | PM/PM10/PM2.5 | PM/PM10/PM2.5 | AVERAGE |
| Testing Date                        |      | 29-Nov-22     | 1-Dec-22      | 2-Dec-22      | -       |
| Stack Temperature                   | °F   | 115           | 104           | 121           | 113     |
| Moisture                            | %    | 1.2%          | 0.7%          | 0.9%          | 0.9%    |
| Velocity                            | ft/s | 84.83         | 83.56         | 86.53         | 84.97   |
| Referenced Flow Rate <sup>[1]</sup> | CFM  | 304,684       | 312,731       | 310,005       | 309,140 |
| Sampling Isokinetic Rate            | %    | 96            | 93            | 94            | 94      |

**Notes:**

[1] Referenced flow rate expressed as dry at 101.3 kPa, 68 °F, and Actual Oxygen

# FINAL REPORT



## GERDAU MACSTEEL, INC

MONROE, MICHIGAN

**MONROE MILL:  
STACK TEST REPORT - ELECTRIC ARC FURNACE (EAF) AND  
LADLE METALLURGY SYSTEM (LMF)**

RWDI #2300259

January 27, 2023

### SUBMITTED TO

**Christopher Hessler**  
Gerdau MacSteel, Inc  
Regional Environmental Manager  
Christopher.Hessler@gerdau.com

**Gerdau MacSteel, Inc**  
**Monroe Mill**  
3000 East Front Street  
Monroe, Michigan 48161  
T: 734.384.6544

**Scott Miller**  
**EGLE, Air Quality Division**  
301 East Louis Glick Highway  
Jackson, Michigan 49201

**TPU Supervisor**  
**EGLE, Air Quality Division**  
Constitution Hall, 2<sup>nd</sup> Floor South  
525 West Allegan Street  
Lansing, Michigan 48933

### SUBMITTED BY

**Brad Bergeron, A.Sc.T., d.E.T.**  
Senior Project Manager | Principal  
Brad.Bergeron@rwdi.com | ext. 2428

**Steve Smith, QSTI**  
Project Manager  
Steve.Smith@rwdi.com | ext. 3703

**RWDI USA LLC**  
**Consulting Engineers & Scientists**  
2239 Star Court  
Rochester Hills, Michigan 48309

T: 248.841.8442  
F: 519.823.1316



[rwdi.com](http://rwdi.com)

This document is intended for the sole use of the party to whom it is addressed and may contain information that is privileged and/or confidential. If you have received this in error, please notify us immediately. Accessible document formats provided upon request. © RWDI name and logo are registered trademarks in Canada and the United States of America.



## EXECUTIVE SUMMARY

RWDI USA LLC (RWDI) has been retained by Gerdau MacSteel, Inc (Gerdau) to complete the emission sampling program at the Gerdau Monroe Mill located at 3000 East Front Street, Monroe, Michigan. The testing evaluated PM, PM2.5, PM10, and Visual Emissions from the EAF and LMF. The test program was completed the week of November 28<sup>th</sup>, 2022.

**Executive Table i:** Average – ROP Limits for FGMELTSHOP - EAF, LMF, and VTD

| Parameter            | Concentration                |                            |
|----------------------|------------------------------|----------------------------|
|                      | Test Average                 | Permit Limit               |
| PM2.5                | 5.06 lb/hr                   | 10.9 lb/hr                 |
| PM2.5                | 0.037 lb/ton of liquid steel | 0.1 lb/ton of liquid steel |
| PM10                 | 7.29 lb/hr                   | 10.9 lb/hr                 |
| PM (Filterable Only) | 0.0014 Grains/dscf           | 0.0018 Grains/dscf         |
| PM (Filterable Only) | 3.24 lb/hr                   | 7.2 lb/hr                  |

**Executive Table ii:** Average – PTI Limits for – EUEAF - EAF Baghouse

| Parameter                            | Concentration      |                    |
|--------------------------------------|--------------------|--------------------|
|                                      | Test Average       | Permit Limit       |
| PM2.5                                | 2.45 lb/hr         | 12.91 lb/hr        |
| PM10                                 | 2.60 lb/hr         | 12.91 lb/hr        |
| PM (Filterable Only)                 | 0.0004 Grains/dscf | 0.0018 Grains/dscf |
| PM (Filterable Only)                 | 0.63 lb/hr         | 7.84 lb/hr         |
| Visual Emissions from Baghouse Stack | 0% Opacity         | 3% Opacity         |
| Visual Emissions from vents/openings | 0% Opacity         | 6% Opacity         |



**Executive Table iii: Average - PTI Limits for - FGLMFVTD - LMF Baghouse**

| Parameter            | Concentration      |                    |
|----------------------|--------------------|--------------------|
|                      | Test Average       | Permit Limit       |
| PM2.5                | 2.61 lb/hr         | 8.95 lb/hr         |
| PM10                 | 4.69 lb/hr         | 8.95 lb/hr         |
| PM (Filterable Only) | 0.0010 Grains/dscf | 0.0018 Grains/dscf |
| PM (Filterable Only) | 2.61 lb/hr         | 3.88 lb/hr         |

**Executive Table iv: Average - ROP Limits for - EUEAF - EAF Baghouse**

| Parameter                                  | Concentration      |                    |
|--|--------------------|--------------------|
|  | Test Average       | Permit Limit       |
| PM (Filterable Only)                       | 0.0004 Grains/dscf | 0.0052 Grains/dscf |
| Visual Emissions from Baghouse Stack       | 0% Opacity         | 3% Opacity         |
| Visual Emissions from Vents and Openings   | 0% Opacity         | 0% Opacity         |
| Visible Emissions from EUEAF Shop Building | 0% Opacity         | 6% Opacity         |

**Executive Table v: Average - ROP Limits for - EULMF - LMF Baghouse**

| Parameter                            | Concentration |              |
|--------------------------------------|---------------|--------------|
|                                      | Test Average  | Permit Limit |
| Visual Emissions from Baghouse Stack | 0% Opacity    | 5% Opacity   |



# FINAL REPORT



## GERDAU MACSTEEL, INC

MONROE, MICHIGAN

**MONROE MILL:  
STACK TEST REPORT - ELECTRIC ARC FURNACE (EAF) AND  
LADLE METALLURGY SYSTEM (LMF)**

RWDI #2300259

January 27, 2023

**SUBMITTED TO**

**Christopher Hessler**  
Gerdau MacSteel, Inc  
Regional Environmental Manager  
Christopher.Hessler@gerdau.com

**Gerdau MacSteel, Inc**  
**Monroe Mill**  
3000 East Front Street  
Monroe, Michigan 48161  
T: 734.384.6544

**Scott Miller**  
**EGLE, Air Quality Division**  
301 East Louis Glick Highway  
Jackson, Michigan 49201

**TPU Supervisor**  
**EGLE, Air Quality Division**  
Constitution Hall, 2<sup>nd</sup> Floor South  
525 West Allegan Street  
Lansing, Michigan 48933

**SUBMITTED BY**

**Brad Bergeron, A.Sc.T., d.E.T.**  
Senior Project Manager | Principal  
Brad.Bergeron@rwdi.com | ext. 2428

**Steve Smith, QSTI**  
Project Manager  
Steve.Smith@rwdi.com | ext. 3703

**RWDI USA LLC**  
**Consulting Engineers & Scientists**  
2239 Star Court  
Rochester Hills, Michigan 48309

T: 248.841.8442  
F: 519.823.1316



[rwdi.com](http://rwdi.com)

This document is intended for the sole use of the party to whom it is addressed and may contain information that is privileged and/or confidential. If you have received this in error, please notify us immediately. Accessible document formats provided upon request. © RWDI name and logo are registered trademarks in Canada and the United States of America.



## EXECUTIVE SUMMARY

RWDI USA LLC (RWDI) has been retained by Gerdau MacSteel, Inc (Gerdau) to complete the emission sampling program at the Gerdau Monroe Mill located at 3000 East Front Street, Monroe, Michigan. The testing evaluated PM, PM2.5, PM10, and Visual Emissions from the EAF and LMF. The test program was completed the week of November 28<sup>th</sup>, 2022.

**Executive Table i:** Average – ROP Limits for FGMELTSHOP - EAF, LMF, and VTD

| Parameter            | Concentration                |                            |
|----------------------|------------------------------|----------------------------|
|                      | Test Average                 | Permit Limit               |
| PM2.5                | 5.06 lb/hr                   | 10.9 lb/hr                 |
| PM2.5                | 0.037 lb/ton of liquid steel | 0.1 lb/ton of liquid steel |
| PM10                 | 7.29 lb/hr                   | 10.9 lb/hr                 |
| PM (Filterable Only) | 0.0014 Grains/dscf           | 0.0018 Grains/dscf         |
| PM (Filterable Only) | 3.24 lb/hr                   | 7.2 lb/hr                  |

**Executive Table ii:** Average – PTI Limits for – EUEAF - EAF Baghouse

| Parameter                            | Concentration      |                    |
|--------------------------------------|--------------------|--------------------|
|                                      | Test Average       | Permit Limit       |
| PM2.5                                | 2.45 lb/hr         | 12.91 lb/hr        |
| PM10                                 | 2.60 lb/hr         | 12.91 lb/hr        |
| PM (Filterable Only)                 | 0.0004 Grains/dscf | 0.0018 Grains/dscf |
| PM (Filterable Only)                 | 0.63 lb/hr         | 7.84 lb/hr         |
| Visual Emissions from Baghouse Stack | 0% Opacity         | 3% Opacity         |
| Visual Emissions from vents/openings | 0% Opacity         | 6% Opacity         |



**Executive Table iii: Average – PTI Limits for – FGLMFVTD – LMF Baghouse**

| Parameter            | Concentration      |                    |
|----------------------|--------------------|--------------------|
|                      | Test Average       | Permit Limit       |
| PM2.5                | 2.61 lb/hr         | 8.95 lb/hr         |
| PM10                 | 4.69 lb/hr         | 8.95 lb/hr         |
| PM (Filterable Only) | 0.0010 Grains/dscf | 0.0018 Grains/dscf |
| PM (Filterable Only) | 2.61 lb/hr         | 3.88 lb/hr         |

**Executive Table iv: Average – ROP Limits for – EUEAF – EAF Baghouse**

| Parameter                                  | Concentration      |                    |
|--|--------------------|--------------------|
|  | Test Average       | Permit Limit       |
| PM (Filterable Only)                       | 0.0004 Grains/dscf | 0.0052 Grains/dscf |
| Visual Emissions from Baghouse Stack       | 0% Opacity         | 3% Opacity         |
| Visual Emissions from Vents and Openings   | 0% Opacity         | 0% Opacity         |
| Visible Emissions from EUEAF Shop Building | 0% Opacity         | 6% Opacity         |

**Executive Table v: Average – ROP Limits for – EULMF – LMF Baghouse**

| Parameter                            | Concentration |              |
|--------------------------------------|---------------|--------------|
|                                      | Test Average  | Permit Limit |
| Visual Emissions from Baghouse Stack | 0% Opacity    | 5% Opacity   |



# TABLE OF CONTENTS

|          |   |          |
|----------|---|----------|
| <b>1</b> | <b>INTRODUCTION .....</b>   | <b>1</b> |
| 1.1      | Location and Dates of Testing.....  | 1        |
| 1.2      | Purpose of Testing.....   | 1        |
| 1.3      | Description of Source.....  | 1        |
| 1.4      | Personnel Involved in Testing .....   | 2        |
| <b>2</b> | <b>SUMMARY OF RESULTS.....</b>  | <b>3</b> |
| 2.1      | Operating Data.....   | 3        |
| 2.2      | Applicable Permit Number .....  | 3        |
| <b>3</b> | <b>SOURCE DESCRIPTION .....</b>   | <b>3</b> |
| 3.1      | Description of Process and Emission Control Equipment.....                                  | 3        |
| 3.2      | Process Flow Sheet or Diagram (if applicable).....  | 3        |
| 3.3      | Type and Quantity of Raw and Finished Materials.....  | 3        |
| 3.4      | Normal Rated Capacity of Process.....   | 3        |
| 3.5      | Process Instrumentation Monitored During the Test.....                                      | 4        |
| <b>4</b> | <b>SAMPLING AND ANALYTICAL PROCEDURES .....</b>   | <b>4</b> |
| 4.1      | Description of Sampling Train and Field Procedures.....                                     | 4        |
| 4.1.1    | Stack Velocity, Temperature, and Volumetric Flow Rate Determination (USEPA Method 1-4)..... | 4        |
| 4.1.2    | Sampling for PM/PM2.5/PM10/CPM (USEPA Method 201A/202) .....                                | 5        |
| 4.2      | Description of Recovery and Analytical Procedures .....                                     | 5        |
| 4.3      | Sampling Port Description.....  | 5        |
| <b>5</b> | <b>TEST RESULTS AND DISCUSSION .....</b>  | <b>6</b> |
| 5.1      | Detailed Results.....   | 6        |
| 5.2      | Discussion of Results.....  | 7        |

**MONROE MILL LMF AND EAF  
GERDAU MACSTEEL**

RWDI#2300259  
January 27, 2023



|      |   |   |
|------|---|---|
| 5.3  | Variations in Testing Procedures.....           | 7 |
| 5.4  | Process Upset Conditions During Testing.....    | 8 |
| 5.5  | Maintenance Performed in Last Three Months..... | 8 |
| 5.6  | Re-Test.....                                    | 8 |
| 5.7  | Audit Samples.....                              | 8 |
| 5.8  | Field Data Sheets .....                         | 8 |
| 5.9  | Calibration Sheets .....                        | 8 |
| 5.10 | Sample Calculations .....                       | 8 |
| 5.11 | Laboratory Data .....                           | 8 |



## LIST OF TABLES (TABLE SECTION)

|                  |  |
|------------------|--|
| <b>Table 1:</b>  | Summary of Sampling Parameters and Methodology                             |
| <b>Table 2A:</b> | Sampling Summary and Sample Log (PM/PM10/PM2.5)                            |
| <b>Table 2B:</b> | Sampling Summary and Sample Log (Visible Emissions)                        |
| <b>Table 3A:</b> | Sampling Summary – Flow Characteristics SVBH-01-Stack 2 (EAF – East White) |
| <b>Table 3B:</b> | Sampling Summary – Flow Characteristics SVBH-01-Stack 1 (EAF – West Red)   |
| <b>Table 3C:</b> | Sampling Summary – Flow Characteristics SVBHLMF-Stack (LMF)                |
| <b>Table 4A:</b> | Average – ROP Limits for FGMELTSHOP – EAF, LMF, VTD                        |
| <b>Table 4B:</b> | Average – PTI Limits for EUEAF – EAF Baghouse                              |
| <b>Table 4C:</b> | Average – PTI Limits for FGLMFVTD – LMF Baghouse                           |
| <b>Table 4D:</b> | Average – ROP Limits for EUEAF – EAF Baghouse                              |
| <b>Table 4E:</b> | Average – ROP Limits for EULMF – LMF Baghouse                              |
| <b>Table 5:</b>  | Opacity – Averaged Results   |

## LIST OF TABLES (IN REPORT)

|                   |  |   |
|-------------------|--|---|
| <b>Table 1.4:</b> | List of Testing Personnel.....                               | 2 |
| <b>Table 4.3:</b> | Summary of Stack Parameters.....                             | 5 |
| <b>Table 5.1:</b> | Average – ROP Limits for FGMELTSHOP - EAF, LMF, and VTD..... | 6 |
| <b>Table 5.2:</b> | Average – PTI Limits for – EUEAF - EAF Baghouse.....         | 6 |
| <b>Table 5.3:</b> | Average – PTI Limits for – FGLMFVTD – LMF Baghouse.....      | 7 |
| <b>Table 5.4:</b> | Average – ROP Limits for – EUEAF – EAF Baghouse.....         | 7 |
| <b>Table 5.5:</b> | Average – ROP Limits for – EULMF – LMF Baghouse.....         | 7 |

## LIST OF FIGURES (FIGURES TAB)

|                  |   |
|------------------|---|
| <b>Figure 1:</b> | EAF East/White Traverse Point Diagram     |
| <b>Figure 2:</b> | EAF West/Red Traverse Point Diagram       |
| <b>Figure 3:</b> | LMF Traverse Point Diagram                |
| <b>Figure 4:</b> | USEPA Method 1-4, 201A/202 Sampling Train |

RECEIVED  
FEB 07 2023  
AIR QUALITY DIVISION



## LIST OF APPENDICES

- Appendix A:** Test Plan and Approval Letter
- Appendix B:** EAF East/White Data
  - Appendix B-1:** EAF East/White Data – PM2.5 and PM10
  - Appendix B-2:** EAF East/White Data – PM (Front Half Only)
  - Appendix B-3:** EAF East/White – Spreadsheets and Field Notes
- Appendix C:** EAF West/Red Data
  - Appendix C-1:** EAF West/Red Data – PM2.5 and PM10
  - Appendix C-2:** EAF West/Red Data – PM (Front Half Only)
  - Appendix C-3:** EAF West/Red – Spreadsheets and Field Notes
- Appendix D:** LMF Data
  - Appendix D-1:** LMF Data – PM2.5 and PM10
  - Appendix D-2:** LMF Data – PM (Front Half Only)
  - Appendix D-3:** LMF – Spreadsheets and Field Notes
- Appendix E:** Visual Emission Data
- Appendix F:** Calibration Documents
- Appendix G:** Sample Calculations
- Appendix H:** Analytical Data
- Appendix I:** Process Data



# 1 INTRODUCTION

RWDI USA LLC (RWDI) has been retained by Gerdau MacSteel, Inc (Gerdau) to complete the emission sampling program at the Gerdau Monroe Mill located at 3000 East Front Street, Monroe, Michigan. The testing evaluated PM, PM<sub>10</sub>, PM<sub>2.5</sub>, and Visual Emissions from the Electric Arc Furnace (EAF) and Ladle Metallurgic Furnace (LMF).

## 1.1 Location and Dates of Testing

The test program was completed at the Gerdau Monroe Mill the week of November 28<sup>th</sup>, 2022.

## 1.2 Purpose of Testing

The purpose of this test program was conducted per PTI 75-18 and MI-ROP-B7061-2016.

## 1.3 Description of Source

Gerdau Monroe Mill is a producer of Special Bar Quality (SBQ) steel. The steel-melting process utilizes Electric Arc Furnace Technology (EAF). The EAF is a refractory-lined cylindrical vessel made of steel plates and having a bowl-shaped hearth and a dome-shaped roof. Water-cooled panels are used for the shell and roof to improve refractory efficiency. Three electrodes, powered by a transformer, are mounted on a superstructure above the furnace and are lowered and raised through ports in the furnace roof. The electrode conveys the energy for melting the scrap steel. Supplemental energy is provided by an oxy-fuel burner and an oxygen/coke lance which swings into the slag door area and operates during the melting/refining process. The furnace is mounted on curved rockers, which allow tilting for slagging and bottom tapping. The EAF melts scrap metal in a batch operation referred to as a heat.

The LMF is a complete ladle metallurgy system which includes arc reheating, alloy additions, powder injections and stirring.





## 1.4 Personnel Involved in Testing

**Table 1.4:** Testing Personnel

|   |  |                       |
|---|--|-----------------------|
| <p><b>Christopher Hessler</b><br/>Regional Environmental Manager<br/>Christopher.Hessler@gerdau.com</p> | <p><b>Gerdau MacSteel, Inc</b></p>   | <p>(734) 384-6544</p> |
| <p><b>Brad Bergeron</b><br/>Senior Project Manager<br/>Brad.Bergeron@rwdi.com</p>                       | <p><b>RWDI USA LLC</b><br/>2239 Star Court<br/>Rochester Hills, MI<br/>48309</p> | <p>(519) 817-9888</p> |
| <p><b>Steve Smith</b><br/>Project Manager<br/>Steve.Smith@rwdi.com</p>                                  |  | <p>(971) 940-5038</p> |
| <p><b>Mason Sakshaug</b><br/>Senior Scientist<br/>Mason.Sakshaug@rwdi.com</p>                           |  | <p>(989) 323-0355</p> |
| <p><b>Michael Nummer</b><br/>Senior Field Technician<br/>Michael.Nummer@rwdi.com</p>                    |  | <p>(586) 863-8237</p> |
| <p><b>Ben Durham</b><br/>Senior Field Technician<br/>Ben.Durham@rwdi.com</p>                            |  | <p>(734) 474-1731</p> |
| <p><b>Juan Vargas</b><br/>Environmental Engineer<br/>Juan.Vargas@rwdi.com</p>                           |  | <p>(513) 293-3180</p> |
| <p><b>Hunter Griggs</b><br/>Field Technician<br/>Hunter.Griggs@rwdi.com</p>                             |  | <p>(810) 441-8351</p> |
| <p><b>Austin Kingsley</b><br/>Field Technician<br/>Austin.Kingsley@rwdi.com</p>                         |  | <p>(586) 863-3553</p> |



## 2 SUMMARY OF RESULTS

### 2.1 Operating Data

Gerdaul personnel made sure the process was operating correctly and production was at acceptable capacity.

### 2.2 Applicable Permit Number

MI-ROP-B7061-2016 and PTI 75-18.

## 3 SOURCE DESCRIPTION

### 3.1 Description of Process and Emission Control Equipment

Emissions from the processes within the Melt Shop are directed to two baghouses (DVBAGHOUSE-01 and DVLMFBAGHOUSE). DVBAGHOUSE-01 serves EUEAF and also accepts emissions captured by the canopy hood in the Melt Shop. DVBAGHOUSE-01 is a positive pressure baghouse with reverse air cleaning. Three main exhaust fans and one direct evacuation control (DEC) fan. The baghouse is equipped with two exhaust stacks, SVBH-01-STACK1 and SVBH-01-STACK2. CO is combusted in the DEC combustion chamber. Screw conveyors transfer the collected baghouse dust to a pneumatic conveying system which transfers the dust into a silo for storage until removed from the site. The second baghouse (DVLMFBAGHOUSE) serves the LMF and VTD operations in the Melt Shop. DVLMFBAGHOUSE is a positive pressure baghouse with reverse air cleaning and is equipped with a single exhaust stack. Dust collected by DVLMFBAGHOUSE is stored in the baghouse hoppers until it is removed from the site.

Fugitive emissions from within the Melt Shop that reach the roof top monitors are captured and directed to the LMF Baghouse.

### 3.2 Process Flow Sheet or Diagram (if applicable)

A process flow diagram can be sent upon request.

### 3.3 Type and Quantity of Raw and Finished Materials

Scrap steel is charged per heat into the EAF. During the heat, additives, alloys, and fluxes are added.

### 3.4 Rated Capacity of Process

Maximum rated capacity is 130 tons of liquid steel produced per heat.



### 3.5 Process Instrumentation Monitored During the Test

Operators regulate the process and control production rates.

- Cast Rate (tons/hr)
- Tap Amounts (tons)

## 4 SAMPLING AND ANALYTICAL PROCEDURES

### 4.1 Description of Sampling Train and Field Procedures

The emission test program will utilize the following test methods codified at Title 40, Part 60, Appendix A of the Code of Federal Regulations (40 CFR 60, Appendix A):

- Method 1 – Sample and Velocity Traverses for Stationary Sources
- Method 2 – Determination of Stack Gas Velocity and Volumetric Flowrate
- Method 3 – Determination of Molecular Weight of Dry Stack Gases (by Fyrite)
- Method 4 – Determination of Moisture Content in Stack Gases
- Method 201A – Determination of PM/PM2.5/PM10 from Stationary Sources
- Method 202 – Determination of Condensable Particulate Matter from Stationary Sources
- Method 9 – Visual Emissions from Stationary Sources

#### 4.1.1 Stack Velocity, Temperature, and Volumetric Flow Rate Determination (USEPA Method 1-4)

Traverse points and determination of upstream and downstream distances from flow disturbance were determined using U.S. EPA Method 1.

The exhaust velocities and flow rates were determined following U.S. EPA Method 2, "Determination of Stack Gas Velocity and Volumetric Flow Rate (Type S Pitot Tube)". Velocity measurements were taken with a pre-calibrated S-Type pitot tube and incline manometer or digital manometer. Volumetric flow rates were determined following the equal area method as outlined in U.S. EPA Method 2. Temperature measurements were made simultaneously with the velocity measurements and were conducted using a chromel-alumel type "k" thermocouple in conjunction with a calibrated digital temperature indicator.

The dry molecular weight of the stack gas was determined following calculations outlined in U.S. EPA Method 3, using a fyrite.

Stack moisture content was determined through direct condensation and according to U.S. EPA Method 4, "Determination of Moisture Content of Stack Gases". Method 4 was conducted through the 201A/202 train.



#### 4.1.2 Sampling for PM/PM<sub>10</sub>/PM<sub>2.5</sub>/CPM (USEPA Method 201A/202)

Three (3) 240-minute tests were performed on SVBH-01-Stack-01 (EAF West (Red)), SVBH-01-Stack-02 (EAF East (White)) and SVBHLMF-Stack (LMF). All tests were completed simultaneously. RWDI's USEPA Method 201A/202 sampling train consists of (1) a stainless steel nozzle, (2) a stainless steel PM<sub>10</sub> cyclone head, (3) a stainless steel PM<sub>2.5</sub> cyclone head, (4) an in stack filter housing, (5) a borosilicate glass probe or liner, (6) a vertical condenser, (7) an empty pot-bellied impinger, (8) an empty modified Greenburg-Smith (GS) impinger, (9) Teflon filter, (10) a second modified GS impinger with 100 ml of water and a third impinger containing silica gel, (11) a sample line and meter box. USEPA Method 201A collects the filterable fractions of PM/PM<sub>10</sub>/PM<sub>2.5</sub> and USEPA Method 202 collects the condensable fraction of PM<sub>10</sub> and PM<sub>2.5</sub>.

A sampling train leak check was conducted before and after each test. After completion of each test, the filter was recovered, the nozzle, PM<sub>10</sub>, and PM<sub>2.5</sub> head were recovered into clean sample jars following USEPA Method 201A. The impinger train was purged with nitrogen for one hour at a flowrate of 14 liters per minute. After the purge, all the glassware was recovered per USEPA Method 202.

## 4.2 Description of Recovery and Analytical Procedures

The samples were all recovered following USEPA Method 201A and 202.

## 4.3 Sampling Port Description

The sampling locations are all outside.

**Table 4.3:** Summary of Exhaust Parameters

| Source  | Diameter (in.) | Approximate Duct Diameters from Flow Disturbance | Number of Ports | Points per Traverse | Total Points per Test |
|---|----------------|--|-----------------|---------------------|-----------------------|
| SVBH-01-Stack-01<br>EUEAF Baghouse<br>Stack 1<br>(EAF West (Red))   | 135            | ~2.6 downstream<br>and 2.7 upstream              | 4               | 12                  | 24                    |
| SVBH-01-Stack-02<br>EUEAF Baghouse<br>Stack 2<br>(EAF East (White)) | 135.5          | ~2.6 downstream<br>and ~2.7 upstream             | 4               | 12                  | 24                    |
| SVBHLMF-Stack<br>LMF Baghouse<br>(LMF)                              | 110            | >8 downstream<br>and >2 upstream                 | 4               | 6                   | 12                    |



## 5 TEST RESULTS AND DISCUSSION

### 5.1 Detailed Results

**Table 5.1:** Average – ROP Limits for FGMELTSHOP - EAF, LMF, and VTD

| Parameter            | Concentration                |                            |
|----------------------|------------------------------|----------------------------|
|                      | Test Average                 | Permit Limit               |
| PM2.5                | 5.06 lb/hr                   | 10.9 lb/hr                 |
| PM2.5                | 0.037 lb/ton of liquid steel | 0.1 lb/ton of liquid steel |
| PM10                 | 7.29 lb/hr                   | 10.9 lb/hr                 |
| PM (Filterable Only) | 0.0014 Grains/dscf           | 0.0018 Grains/dscf         |
| PM (Filterable Only) | 3.24 lb/hr                   | 7.2 lb/hr                  |

**Table 5.2:** Average – PTI Limits for – EUEAF - EAF Baghouse

| Parameter                            | Concentration      |                    |
|--------------------------------------|--------------------|--------------------|
|                                      | Test Average       | Permit Limit       |
| PM2.5                                | 2.45 lb/hr         | 12.91 lb/hr        |
| PM10                                 | 2.60 lb/hr         | 12.91 lb/hr        |
| PM (Filterable Only)                 | 0.0004 Grains/dscf | 0.0018 Grains/dscf |
| PM (Filterable Only)                 | 0.63 lb/hr         | 7.84 lb/hr         |
| Visual Emissions from Baghouse Stack | 0% Opacity         | 3% Opacity         |
| Visual Emissions from vents/openings | 0% Opacity         | 6% Opacity         |

RECEIVED  
FEB 07 2023  
AIR QUALITY DIVISION



**Table 5.3:** Average – PTI Limits for – FGLMFVTD – LMF Baghouse

| Parameter            | Concentration      |                    |
|----------------------|--------------------|--------------------|
|                      | Test Average       | Permit Limit       |
| PM2.5                | 2.61 lb/hr         | 8.95 lb/hr         |
| PM10                 | 4.69 lb/hr         | 8.95 lb/hr         |
| PM (Filterable Only) | 0.0010 Grains/dscf | 0.0018 Grains/dscf |
| PM (Filterable Only) | 2.61 lb/hr         | 3.88 lb/hr         |

**Table 5.4:** Average – ROP Limits for – EUEAF – EAF Baghouse

| Parameter                                  | Concentration      |                    |
|--|--------------------|--------------------|
|  | Test Average       | Permit Limit       |
| PM (Filterable Only)                       | 0.0004 Grains/dscf | 0.0052 Grains/dscf |
| Visual Emissions from Baghouse Stack       | 0% Opacity         | 3% Opacity         |
| Visual Emissions from Vents and Openings   | 0% Opacity         | 0% Opacity         |
| Visible Emissions from EUEAF Shop Building | 0% Opacity         | 6% Opacity         |

**Table 5.5:** Average – ROP Limits for – EULMF – LMF Baghouse

| Parameter                            | Concentration |              |
|--------------------------------------|---------------|--------------|
|                                      | Test Average  | Permit Limit |
| Visual Emissions from Baghouse Stack | 0% Opacity    | 5% Opacity   |

## 5.2 Discussion of Results

The detailed results can be found in **Appendices B, C, D, and E**. Note, the laboratory detected visible solid residue in LMF T1 <10 to >2.5 fraction of the acetone rinse from USEPA Method 201A. The data was used as is for the report. We believe this was an unrelated to the process emissions.

## 5.3 Variations in Testing Procedures

There were not testing variations.



## 5.4 Process Upset Conditions During Testing

There were no process upsets.

## 5.5 Maintenance Performed in Last Three Months

There has been no significant maintenance on the EAF or LMF in the last three months. Normal routine maintenance is completed as scheduled.

## 5.6 Re-Test

This was not a retest.

## 5.7 Audit Samples

This test did not require any audit samples.

## 5.8 Field Data Sheets

Field data sheets can be found in **Appendices B, C, D, and E.**

## 5.9 Calibration Sheets

Calibration sheets can be found in **Appendix F.**


## 5.10 Sample Calculations

Sample calculations can be found in **Appendix G.**

## 5.11 Laboratory Data

Laboratory data can be found in **Appendix H.**

# TABLES





**Table 1: Summary of Sampling Parameters and Methodology**

| Source Location                       | No. of Tests per Stack | Sampling Parameter                   | Sampling Method                            |
|---------------------------------------|------------------------|--------------------------------------|--|
| SVBH-01-Stack 2<br>EAF - East (White) | 3                      | Velocity, Temperature and Flow Rate  | U.S. EPA <sup>[1]</sup> Methods 1-4        |
|                                       | 3                      | Total Particulate Matter             | U.S. EPA [1] Method 201A (Filterable Only) |
|                                       | 3                      | PM <sub>10</sub> / PM <sub>2.5</sub> | U.S. EPA [1] Method 201A/202               |
|                                       | 3                      | Oxygen, Carbon Dioxide               | U.S. EPA [1] Method 3                      |
|                                       | 3                      | Visible Emissions                    | U.S. EPA [1] Method 9                      |
| SVBH-01-Stack 1<br>EAF - West (Red)   | 3                      | Velocity, Temperature and Flow Rate  | U.S. EPA <sup>[1]</sup> Methods 1-4        |
|                                       | 3                      | Total Particulate Matter             | U.S. EPA [1] Method 201A (Filterable Only) |
|                                       | 3                      | PM <sub>10</sub> / PM <sub>2.5</sub> | U.S. EPA [1] Method 201A/202               |
|                                       | 3                      | Oxygen, Carbon Dioxide               | U.S. EPA [1] Method 3                      |
|                                       | 3                      | Visible Emissions                    | U.S. EPA [1] Method 9                      |
| SVBHLMF-Stack<br>LMF                  | 3                      | Velocity, Temperature and Flow Rate  | U.S. EPA <sup>[1]</sup> Methods 1-4        |
|                                       | 3                      | Total Particulate Matter             | U.S. EPA [1] Method 201A (Filterable Only) |
|                                       | 3                      | PM <sub>10</sub> / PM <sub>2.5</sub> | U.S. EPA [1] Method 201A/202               |
|                                       | 3                      | Oxygen, Carbon Dioxide               | U.S. EPA [1] Method 3                      |
|                                       | 3                      | Visible Emissions                    | U.S. EPA [1] Method 9                      |

**Notes:**

[1] U.S. EPA - United States Environmental Protection Agency

**Table 2A: Sampling Summary and Sample Log (PM/PM10/PM2.5)**

| Source and Test #   | Sampling Date | Start Time | End Time | Filter ID / Trap ID |
|---|---------------|------------|----------|---------------------|
| <b>SVBH-01-Stack 2 (EAF - East (White)) - Velocity / Total Particulate / PM10 / PM2.5</b> |               |            |          |                     |
| Blank   | 2-Dec-22      | -          | -        | QZ 47-35            |
| Test #1   | 29-Nov-22     | 9:15 AM    | 1:25 PM  | QZ 47-18            |
| Test #2   | 1-Dec-22      | 8:21 AM    | 12:41 PM | QZ 47-36            |
| Test #3   | 2-Dec-22      | 9:15 AM    | 2:12 PM  | QZ 47-33            |
| <b>SVBH-01-Stack 1 (EAF - West (Red)) - Velocity / Total Particulate / PM10 / PM2.5</b>   |               |            |          |                     |
| Blank   | 2-Dec-22      | -          | -        | QZ 47-35            |
| Test #1   | 29-Nov-22     | 9:15 AM    | 1:31 PM  | QZ 47-40            |
| Test #2   | 1-Dec-22      | 8:21 AM    | 12:42 PM | QZ 47-39            |
| Test #3   | 2-Dec-22      | 9:15 AM    | 2:05 PM  | QZ 47-34            |
| <b>SVBHLMF-Stack (LMF) - Velocity / Total Particulate / PM10 / PM2.5</b>                  |               |            |          |                     |
| Blank   | 2-Dec-22      | -          | -        | QZ 47-35            |
| Test #1   | 29-Nov-22     | 9:15 AM    | 1:47 PM  | QZ 47-9             |
| Test #2   | 1-Dec-22      | 8:21 AM    | 1:12 PM  | QZ 47-38            |
| Test #3   | 2-Dec-22      | 9:15 AM    | 2:42 PM  | QZ 47-32            |

**Table 2B: Sampling Summary and Sample Log (Visible Emissions)**

| Source and Test #   | Sampling Date | Start Time | End Time |
|---|---------------|------------|----------|
| <b>SVBH-01-Stack 2 (EAF - East (White)) - Visible Emissions</b> |               |            |          |
| Test #1   | 1-Dec-22      | 8:57 AM    | 9:56 AM  |
| Test #2   | 1-Dec-22      | 9:59 AM    | 10:59 AM |
| Test #3   | 2-Dec-22      | 9:20 AM    | 10:20 AM |
| <b>SVBH-01-Stack 1 (EAF - West (Red)) - Visible Emissions</b>   |               |            |          |
| Test #1   | 1-Dec-22      | 8:58 AM    | 9:57 AM  |
| Test #2   | 1-Dec-22      | 10:00 AM   | 11:00 AM |
| Test #3   | 2-Dec-22      | 9:20 AM    | 10:20 AM |
| <b>SVBHLMF-Stack (LMF) - Visible Emissions</b>                  |               |            |          |
| Test #1   | 1-Dec-22      | 8:57 AM    | 9:56 AM  |
| Test #2   | 1-Dec-22      | 9:59 AM    | 10:59 AM |
| Test #3   | 2-Dec-22      | 9:20 AM    | 10:20 AM |

**Table 3A: Sampling Summary - Flow Characteristics**  
**SVBH-01-Stack 2 (EAF - EAST (White))**

| Stack Gas Parameter                 |      | Test No. 1    | Test No. 2    | Test No. 3    | TOTAL<br>AVERAGE |
|-------------------------------------|------|---------------|---------------|---------------|------------------|
|                                     |      | PM/PM10/PM2.5 | PM/PM10/PM2.5 | PM/PM10/PM2.5 |                  |
| Testing Date                        |      | 29-Nov-22     | 1-Dec-22      | 2-Dec-22      | -                |
| Stack Temperature                   | °F   | 185           | 172           | 176           | 178              |
| Moisture                            | %    | 2.3%          | 1.5%          | 1.4%          | 1.7%             |
| Velocity                            | ft/s | 41.47         | 40.80         | 42.87         | 41.71            |
| Referenced Flow Rate <sup>[3]</sup> | CFM  | 195,425       | 205,455       | 208,171       | 203,017          |
| Sampling Isokinetic Rate            | %    | 103           | 103           | 99            | 102              |

**Notes:**

[1] Referenced flow rate expressed as dry at 101.3 kPa, 68 °F, and Actual Oxygen

**Table 3B: Sampling Summary - Flow Characteristics**  
**SVBH-01-Stack 1 (EAF - West (Red))**

| Stack Gas Parameter                 |      | Test No. 1    | Test No. 2    | Test No. 3    | TOTAL   |
|-------------------------------------|------|---------------|---------------|---------------|---------|
|                                     |      | PM/PM10/PM2.5 | PM/PM10/PM2.5 | PM/PM10/PM2.5 | AVERAGE |
| Testing Date                        |      | 29-Nov-22     | 1-Dec-22      | 2-Dec-22      | -       |
| Stack Temperature                   | °F   | 189           | 174           | 180           | 181     |
| Moisture                            | %    | 2.6%          | 1.3%          | 1.9%          | 1.9%    |
| Velocity                            | ft/s | 37.76         | 36.43         | 37.14         | 37.11   |
| Referenced Flow Rate <sup>[3]</sup> | CFM  | 175,372       | 178,302       | 177,236       | 176,970 |
| Sampling Isokinetic Rate            | %    | 99            | 98            | 97            | 98      |

**Notes:**

[3] Referenced flow rate expressed as dry at 101.3 kPa, 68 °F, and Actual Oxygen

**Table 3C: Sampling Summary - Flow Characteristics**  
**SVBHLMF-Stack (LMF)**

| Stack Gas Parameter                 |      | Test No. 1    | Test No. 2    | Test No. 3    | TOTAL   |
|-------------------------------------|------|---------------|---------------|---------------|---------|
|                                     |      | PM/PM10/PM2.5 | PM/PM10/PM2.5 | PM/PM10/PM2.5 | AVERAGE |
| Testing Date                        |      | 29-Nov-22     | 1-Dec-22      | 2-Dec-22      | -       |
| Stack Temperature                   | °F   | 115           | 104           | 121           | 113     |
| Moisture                            | %    | 1.2%          | 0.7%          | 0.9%          | 0.9%    |
| Velocity                            | ft/s | 84.83         | 83.56         | 86.53         | 84.97   |
| Referenced Flow Rate <sup>[1]</sup> | CFM  | 304,684       | 312,731       | 310,005       | 309,140 |
| Sampling Isokinetic Rate            | %    | 96            | 93            | 94            | 94      |

**Notes:**

[1] Referenced flow rate expressed as dry at 101.3 kPa, 68 °F, and Actual Oxygen

**Table 4A: Average – ROP Limits for FGMELTSHOP - EAF, LMF, and VTD**

| Parameter            | Concentration                |                            |
|----------------------|------------------------------|----------------------------|
|                      | Test Average                 | Permit Limit               |
| PM <sub>2.5</sub>    | 5.06 lb/hr                   | 10.9 lb/hr                 |
| PM <sub>2.5</sub>    | 0.037 lb/ton of liquid steel | 0.1 lb/ton of liquid steel |
| PM <sub>10</sub>     | 7.29 lb/hr                   | 10.9 lb/hr                 |
| PM (Filterable Only) | 0.0014 Grains/dscf           | 0.0018 Grains/dscf         |
| PM (Filterable Only) | 3.24 lb/hr                   | 7.2 lb/hr                  |

**Table 4B: Average – PTI Limits for – EUEAF - EAF Baghouse**

| Parameter                            | Concentration      |                    |
|--------------------------------------|--------------------|--------------------|
|                                      | Test Average       | Permit Limit       |
| PM <sub>2.5</sub>                    | 2.45 lb/hr         | 12.91 lb/hr        |
| PM <sub>10</sub>                     | 2.60 lb/hr         | 12.91 lb/hr        |
| PM (Filterable Only)                 | 0.0004 Grains/dscf | 0.0018 Grains/dscf |
| PM (Filterable Only)                 | 0.63 lb/hr         | 7.84 lb/hr         |
| Visual Emissions from Baghouse Stack | 0% Opacity         | 3% Opacity         |
| Visual Emissions from vents/openings | 0% Opacity         | 6% Opacity         |

**Table 4C: Average – PTI Limits for – FGLMFVTD – LMF Baghouse**

| Parameter            | Concentration      |                    |
|----------------------|--------------------|--------------------|
|                      | Test Average       | Permit Limit       |
| PM <sub>2.5</sub>    | 2.61 lb/hr         | 8.95 lb/hr         |
| PM <sub>10</sub>     | 4.69 lb/hr         | 8.95 lb/hr         |
| PM (Filterable Only) | 0.0010 Grains/dscf | 0.0018 Grains/dscf |
| PM (Filterable Only) | 2.61 lb/hr         | 3.88 lb/hr         |

**RECEIVED**  
**FEB 07 2023**  
**AIR QUALITY DIVISION**

**Table 4D: Average – ROP Limits for – EUEAF – EAF Baghouse**

| Parameter                                  | Concentration      |                    |
|--|--------------------|--------------------|
|  | Test Average       | Permit Limit       |
| PM (Filterable Only)                       | 0.0004 Grains/dscf | 0.0052 Grains/dscf |
| Visual Emissions from Baghouse Stack       | 0% Opacity         | 3% Opacity         |
| Visual Emissions from Vents and Openings   | 0% Opacity         | 0% Opacity         |
| Visible Emissions from EUEAF Shop Building | 0% Opacity         | 6% Opacity         |

**Table 4E: Average – ROP Limits for – EULMF – LMF Baghouse**

| Parameter                            | Concentration |              |
|--------------------------------------|---------------|--------------|
|                                      | Test Average  | Permit Limit |
| Visual Emissions from Baghouse Stack | 0% Opacity    | 5% Opacity   |



**Table 5: Opacity- Averaged Results**

| Parameter                                  | Opacity  |          |          | Average Opacity |
|--|----------|----------|----------|-----------------|
|  | 1-Dec-22 | 1-Dec-22 | 1-Dec-22 |                 |
|  | (%)      | (%)      | (%)      | (%)             |
| <b>SVBH-01-Stack-02 (EAF East (White))</b> |          |          |          |                 |
| Opacity                                    | 0        | 0        | 0        | 0               |
| <b>SVBH-01-Stack-01 (EAF West (Red))</b>   |          |          |          |                 |
| Opacity                                    | 0        | 0        | 0        | 0               |
| <b>SVBHLMF-Stack (LMF)</b>                 |          |          |          |                 |
| Opacity                                    | 0        | 0        | 0        | 0               |

# FIGURES

