## MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY AIR QUALITY DIVISION

July 2, 2024

PERMIT TO INSTALL 911-92A

ISSUED TO Acrosa Shoring Products, Inc.

### LOCATED AT 685 Hull Road Mason, Michigan 48854

IN THE COUNTY OF

Ingham

# STATE REGISTRATION NUMBER N3609

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:

# June 7, 2024

DATE PERMIT TO INSTALL APPROVED: July 2, 2024	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

# PERMIT TO INSTALL

## **Table of Contents**

COMMON ACRONYMS	2
POLLUTANT / MEASUREMENT ABBREVIATIONS	3
GENERAL CONDITIONS	4
EMISSION UNIT SPECIAL CONDITIONS	6
EMISSION UNIT SUMMARY TABLE	6
EUCOATING	7
EUWELDING	10

### **COMMON ACRONYMS**

AQD BACT CAA CAM CEMS CFR COMS Department/department/EGLE EU FG GACS GC GHGS HVLP ID IRSL ITSL LAER MACT MAERS MAP MSDS NA NAAQS NESHAP NSPS NSR PS SS NSR PS SS NSR PS SC SCR SCR SCR SCR SCR SCR SCR SCR SCR	Air Quality Division Best Available Control Technology Clean Air Act Compliance Assurance Monitoring Continuous Emission Monitoring System Code of Federal Regulations Continuous Opacity Monitoring System Michigan Department of Environment, Great Lakes, and Energy Emission Unit Flexible Group Gallons of Applied Coating Solids General Condition Greenhouse Gases High Volume Low Pressure* Identification Initial Risk Screening Level Lowest Achievable Emission Rate Maximum Achievable Control Technology Michigan Air Emissions Reporting System Malfunction Abatement Plan Material Safety Data Sheet Not Applicable National Ambient Air Quality Standards National Emission Standard for Hazardous Air Pollutants New Source Performance Standards New Source Review Performance Specification Prevention of Significant Deterioration Permanent Total Enclosure Permit to Install Reasonable Available Control Technology Renewable Operating Permit Special Condition Selective Catalytic Reduction Selective Catalytic Reduction State Registration Number To Be Determined Toxicity Equivalence Quotient United States Environmental Protection Agency
VE	Visible Emissions

# POLLUTANT / MEASUREMENT ABBREVIATIONS

acfm BTU °C CO CO <sub>2</sub> e	Actual cubic feet per minute British Thermal Unit Degrees Celsius Carbon Monoxide Carbon Dioxide Equivalent
dscf dscm °F	Dry standard cubic foot Dry standard cubic meter Degrees Fahrenheit
gr	Grains
HAP	Hazardous Air Pollutant
Hg	Mercury
hr	Hour
HP	Horsepower
H₂S	Hydrogen Sulfide
kW	Kilowatt
lb	Pound
m	Meter
mg	Milligram
mm	Millimeter
MM	Million
MW	Megawatts
NMOC	Non-Methane Organic Compounds
NOx	Oxides of Nitrogen
ng	Nanogram Particulate Matter
PM PM10	Particulate Matter
PM10 PM2.5	Particulate Matter equal to or less than 10 microns in diameter Particulate Matter equal to or less than 2.5 microns in diameter
pph	Pounds per hour
ppm	Parts per million
ppmv	Parts per million by volume
ppmw	Parts per million by weight
psia	Pounds per square inch absolute
psig	Pounds per square inch gauge
scf	Standard cubic feet
Sec	Seconds
SO <sub>2</sub>	Sulfur Dioxide
TAC	Toxic Air Contaminant
Temp	Temperature
THC	Total Hydrocarbons
tpy	Tons per year
μg	Microgram
μm	Micrometer or Micron
VOC	Volatile Organic Compounds
yr	Year

#### **GENERAL CONDITIONS**

- 1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. (R 336.1201(1))
- 2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. (R 336.1201(4))
- 3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. (R 336.1201(6)(b))
- 4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. (R 336.1201(8), Section 5510 of Act 451, PA 1994)
- 5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy. (R 336.1219)
- 6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. (R 336.1901)
- 7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). (R 336.1912)
- 8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
- 9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
- 10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

- 11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). (R 336.1301)
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
- 12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). (**R 336.1370**)
- 13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. (R 336.2001)

#### **EMISSION UNIT SPECIAL CONDITIONS**

### EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Including Process Equipment & Control Device(s))	Flexible Group ID
EUCOATING	Spray coating operations including four (4) downdraft filtration systems as control.	NA
EUWELDING	Thirty-four (34) metal inert gas (MIG) welding stations and twelve (12) portable MIG welding units.	NA

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

# EUCOATING EMISSION UNIT CONDITIONS

#### **DESCRIPTION**

Spray coating operations including four (4) downdraft filtration systems as control.

#### Flexible Group ID: NA

#### POLLUTION CONTROL EQUIPMENT

Four (4) downdraft filtration systems for particulate control.

#### I. EMISSION LIMIT(S)

1.	There shall be no visible emissions from EUCOATING.	(R 336.1301)	)
----	---	--------------	---

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
2. VOC	10.7 tpy	12-month rolling time	EUCOATING	SC V.1	R 336.1702(a)
		period as determined at		SC VI.3	
		the end of each calendar		SC VI.4	
		month			

#### II. MATERIAL LIMIT(S)

Material	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOC	3.5 lb/gal (minus water) <sup>a</sup> as applied	Instantaneous	EUCOATING	SC V.1	R 336.1702(a)

<sup>a</sup> The phrase "minus water" shall also include compounds which are used as organic solvents and which are excluded from the definition of volatile organic compound.

#### III. PROCESS/OPERATIONAL RESTRICTION(S)

- 1. The permittee shall capture all waste coatings and shall store them in closed containers. The permittee shall dispose of all waste coatings in an acceptable manner in compliance with all applicable state rules and federal regulations. (R 336.1225, R 336.1702(a))
- 2. The permittee shall dispose of spent filters in a manner which minimizes the introduction of air contaminants to the outer air. (R 336.1224, R 336.1370(1))
- 3. The permittee shall handle all VOC containing materials, including coatings, reducers, solvents and thinners, in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. (R 336.1224, R 336.1225, R 336.1702(a)

#### IV. DESIGN/EQUIPMENT PARAMETER(S)

- 1. The permittee shall not operate EUCOATING unless all respective downdraft filters are installed, maintained, and operated in a satisfactory manner. (R 336.1910)
- The permittee shall equip and maintain EUCOATING with HVLP or comparable technology with equivalent transfer efficiency. For HVLP applicators, the permittee shall keep test caps available for pressure testing. (R 336.1702(a))

### V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

1. The permittee shall determine the VOC content, water content and density of any coating, as applied and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. (R 336.1225, R 336.1702)

#### VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

- 1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15<sup>th</sup> day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1225, R 336.1702)**
- The permittee shall maintain a current listing from the manufacturer of the chemical composition of each coating, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. (R 336.1225, R 336.1702)
- 3. The permittee shall keep the following information on a monthly basis for EUCOATING:
  - a) Gallons (with water) of each coating used.
  - b) VOC content (minus water and with water) of each coating as applied.
  - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
  - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.
  - f) Hours of operations.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file for at least 2 years and make them available to the Department upon request. (R 336.1225, R 336.1702(a))

- 4. The permittee shall keep the following information on a monthly basis for the use of purge and clean-up solvents associated with EUCOATING:
  - a) Gallons of each solvent used and reclaimed.
  - b) VOC content, in pounds per gallon, of each solvent used.
  - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
  - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. (R 336.1225, R 336.1702(a))

#### VII. <u>REPORTING</u>

NA

### VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

	Stack & Vent ID	Maximum Exhaust Diameter / Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1.	SVEP01	36	43.5	R 336.1225, 40 CFR 52.21(c) & (d)
2.	SVEP02	36	43.5	R 336.1225, 40 CFR 52.21(c) & (d)
3.	SVEP03	36	43.5	R 336.1225, 40 CFR 52.21(c) & (d)

# IX. OTHER REQUIREMENT(S)

1. The permittee shall comply with all applicable provisions of the National Emission Standards for Hazardous Air Pollutants, as specified in 40 CFR Part 63, Subpart XXXXX for Nine Metal Fabrication and Finishing Source categories by the initial compliance date. **(40 CFR Part 63, Subpart XXXXXX)** 

#### Footnotes:

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

# EUWELDING EMISSION UNIT CONDITIONS

#### DESCRIPTION

Thirty-four (34) metal inert gas (MIG) welding stations and twelve (12) portable MIG welding units.

#### Flexible Group ID: NA.

#### POLLUTION CONTROL EQUIPMENT

NA

#### I. EMISSION LIMIT(S)

1. Visible emissions from each MIG welding station shall not exceed a six minute average of five percent opacity. (R 336.1301, R 336.1303)

#### II. MATERIAL LIMIT(S)

 The permittee shall not use more than 25,000 pounds of welding feed per month nor 300,000 pounds through EUWELDING per 12 month rolling time period as determined at the end of each calendar month. (R 336.1225, 40 CFR 52.21(c) & (d))

#### III. PROCESS/OPERATIONAL RESTRICTION(S)

NA

#### IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

#### V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

#### VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

- 1. The permittee shall keep a record of the welding feed wire used in EUWELDING on a monthly basis:
  - a) Pounds of welding feed wire used.
  - b) Where applicable, the amount (in pounds) of welding feed wire reclaimed.
  - c) Monthly usage rates of welding feed wire as determined at the end of each calendar month
  - d) Welding feed wire usage rates determining the annual usage rate on a 12-month rolling time period determined at the end of each calendar month.

The permittee shall keep the records on file at the facility in a format acceptable to the AQD District Supervisor and make them available to the Department upon request. (R 336.1225)

#### VII. <u>REPORTING</u>

NA

### VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

NA

# IX. OTHER REQUIREMENT(S)

NA

#### Footnotes:

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).