

**MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY  
AIR QUALITY DIVISION**

August 29, 2024

**PERMIT TO INSTALL**  
110-18B

**ISSUED TO**  
Lacks Enterprises, Inc.

**LOCATED AT**  
4375 52<sup>nd</sup> Street  
Kentwood, Michigan 49512

**IN THE COUNTY OF**  
Kent

**STATE REGISTRATION NUMBER**  
N2079

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:

**April 19, 2024**

DATE PERMIT TO INSTALL APPROVED:

**August 29, 2024**

SIGNATURE:

DATE PERMIT VOIDED:

SIGNATURE:

DATE PERMIT REVOKED:

SIGNATURE:

PERMIT TO INSTALL

Table of Contents

COMMON ACRONYMS .....2

POLLUTANT / MEASUREMENT ABBREVIATIONS.....3

GENERAL CONDITIONS .....4

EMISSION UNIT SPECIAL CONDITIONS.....6

    EMISSION UNIT SUMMARY TABLE .....6

FLEXIBLE GROUP SPECIAL CONDITIONS.....7

    FLEXIBLE GROUP SUMMARY TABLE .....7

FGCENTRALPAINT .....8

## COMMON ACRONYMS

AQD	Air Quality Division
BACT	Best Available Control Technology
CAA	Clean Air Act
CAM	Compliance Assurance Monitoring
CEMS	Continuous Emission Monitoring System
CFR	Code of Federal Regulations
COMS	Continuous Opacity Monitoring System
Department/department/EGLE	Michigan Department of Environment, Great Lakes, and Energy
EU	Emission Unit
FG	Flexible Group
GACS	Gallons of Applied Coating Solids
GC	General Condition
GHGs	Greenhouse Gases
HVLP	High Volume Low Pressure*
ID	Identification
IRSL	Initial Risk Screening Level
ITSL	Initial Threshold Screening Level
LAER	Lowest Achievable Emission Rate
MACT	Maximum Achievable Control Technology
MAERS	Michigan Air Emissions Reporting System
MAP	Malfunction Abatement Plan
MSDS	Material Safety Data Sheet
NA	Not Applicable
NAAQS	National Ambient Air Quality Standards
NESHAP	National Emission Standard for Hazardous Air Pollutants
NSPS	New Source Performance Standards
NSR	New Source Review
PS	Performance Specification
PSD	Prevention of Significant Deterioration
PTE	Permanent Total Enclosure
PTI	Permit to Install
RACT	Reasonable Available Control Technology
ROP	Renewable Operating Permit
SC	Special Condition
SCR	Selective Catalytic Reduction
SNCR	Selective Non-Catalytic Reduction
SRN	State Registration Number
TBD	To Be Determined
TEQ	Toxicity Equivalence Quotient
USEPA/EPA	United States Environmental Protection Agency
VE	Visible Emissions

\*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

## POLLUTANT / MEASUREMENT ABBREVIATIONS

acfm	Actual cubic feet per minute
BTU	British Thermal Unit
°C	Degrees Celsius
CO	Carbon Monoxide
CO <sub>2</sub> e	Carbon Dioxide Equivalent
dscf	Dry standard cubic foot
dscm	Dry standard cubic meter
°F	Degrees Fahrenheit
gr	Grains
HAP	Hazardous Air Pollutant
Hg	Mercury
hr	Hour
HP	Horsepower
H <sub>2</sub> S	Hydrogen Sulfide
kW	Kilowatt
lb	Pound
m	Meter
mg	Milligram
mm	Millimeter
MM	Million
MW	Megawatts
NMOC	Non-Methane Organic Compounds
NO <sub>x</sub>	Oxides of Nitrogen
ng	Nanogram
PM	Particulate Matter
PM <sub>10</sub>	Particulate Matter equal to or less than 10 microns in diameter
PM <sub>2.5</sub>	Particulate Matter equal to or less than 2.5 microns in diameter
pph	Pounds per hour
ppm	Parts per million
ppmv	Parts per million by volume
ppmw	Parts per million by weight
psia	Pounds per square inch absolute
psig	Pounds per square inch gauge
scf	Standard cubic feet
sec	Seconds
SO <sub>2</sub>	Sulfur Dioxide
TAC	Toxic Air Contaminant
Temp	Temperature
THC	Total Hydrocarbons
tpy	Tons per year
µg	Microgram
µm	Micrometer or Micron
VOC	Volatile Organic Compounds
yr	Year

## GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). **(R 336.1301)**
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). **(R 336.1370)**
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. **(R 336.2001)**

## EMISSION UNIT SPECIAL CONDITIONS

### EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Emission Unit ID</b>	<b>Emission Unit Description (Including Process Equipment &amp; Control Device(s))</b>	<b>Installation Date / Modification Date</b>	<b>Flexible Group ID</b>
EUSPINELLE	Pretreatment system for washing parts prior to coating: Includes series of spray cleaning and wash stages, as well as an anodic etch dip tank. The anodic etch dip tank will be exhausted to a chrome composite mesh pad system.	11/4/2019	FGCENTRALPAINT
EUCENTRALPAINT	Exterior plastic automotive parts automatic paint system including a primer booth, a basecoat booth, a clearcoat booth, and one natural gas fired curing oven (in-direct fired oven). VOC emissions from each booth and an oven are captured by using a Permanent Total Enclosure (PTE) and abated via a Regenerative Thermal Oxidizer (RTO). Each paint booth is equipped with a water curtain system to control particulate matter.	11/4/2019	FGCENTRALPAINT, FGSUBPARTPPPP, FGSUBPARTDDDD D
EUSOLRECLAIM	Solvent reclamation system (90% by weight).	3/1/2021	FGCENTRALPAINT

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

FLEXIBLE GROUP SPECIAL CONDITIONS

FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Flexible Group ID	Flexible Group Description	Associated Emission Unit IDs
FGCENTRALPAINT	Pretreatment system, exterior plastic automotive parts automatic paint system, and solvent reclamation system. VOC emissions from EUCENTRALPAINT are captured by using a Permanent Total Enclosure (PTE) and abated via a Regenerative Thermal Oxidizer (RTO). Each paint booth of EUCENTRALPAINT is equipped with a water curtain system to control particulate matter. EUSPINELLE is controlled by a composite mesh pad system with HEPA filter.	EUSPINELLE, EUCENTRALPAINT, EUSOLRECLAIM
Note: Please see MI-ROP-N2079-2017 for all special conditions related to FGSUBPARTPPPP, FGSUBPARTDDDDD, and FGFACILITY		



## FGCENTRALPAINT FLEXIBLE GROUP CONDITIONS

### **DESCRIPTION**

Pretreatment system, exterior plastic automotive parts automatic paint system, and solvent reclamation system.

**Emission Unit:** EUSPINELLE, EUCENTRALPAINT, EUSOLRECLAIM

### **POLLUTION CONTROL EQUIPMENT**

VOC emissions from EUCENTRALPAINT are captured by using a Permanent Total Enclosure (PTE) and abated via a Regenerative Thermal Oxidizer (RTO). Each paint booth of EUCENTRALPAINT is equipped with a water curtain system to control particulate matter. Total chromium emissions from EUSPINELLE are controlled by a composite mesh pad system with HEPA filter.

### **I. EMISSION LIMIT(S)**

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period / Operating Scenario</b>	<b>Equipment</b>	<b>Monitoring / Testing Method</b>	<b>Underlying Applicable Requirements</b>
1. VOC	29.4 tpy	12-month rolling time period as determined at the end of each calendar month	FGCENTRALPAINT	SC VI.2, SC VI.3	R 336.1702(a)
2. Total Chromium <sup>1</sup>	1.06E-04 pph	Hourly	EUSPINELLE portion of FGCENTRALPAINT	SC V.4	R 336.1224, R 336.1225

### **II. MATERIAL LIMIT(S)**

NA

### **III. PROCESS/OPERATIONAL RESTRICTION(S)**

1. The permittee shall recover and reclaim, recycle, or dispose of, in accordance with all applicable regulations, a minimum of 90.0 percent by weight of all purge solvents used in the EUCENTRALPAINT portion of FGCENTRALPAINT. **(R 336.1225, R 336.1702(a))**
2. The permittee shall capture all waste coatings, reducer, purge solvents *etc.* (materials) and shall store them in closed containers. The permittee shall dispose of all waste materials in an acceptable manner in compliance with all applicable state rules and federal regulations. **(R 336.1225, R 336.1702(a))**
3. The permittee shall handle all VOC and / or HAP containing materials in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. **(R 336.1224, R 336.1225, R 336.1702(a))**
4. The permittee shall not operate EUCENTRALPAINT and EUSPINELLE unless a malfunction abatement plan (MAP) as described in Rule 911(2), is implemented and maintained. The MAP shall, at a minimum, specify the following:

- a) A complete preventative maintenance program including identification of the supervisory personnel responsible for overseeing the inspection, maintenance, and repair of air-cleaning devices, a description of the items or conditions that shall be inspected, the frequency of the inspections or repairs, and an identification of the major replacement parts that shall be maintained in inventory for quick replacement.
- b) An identification of the source and operating variables that shall be monitored to detect a malfunction or failure, the normal operating range of these variables, and a description of the method of monitoring or surveillance procedures.
- c) A description of the corrective procedures or operational changes that shall be taken in the event of a malfunction or failure to achieve compliance with the applicable emission limits.

If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. **(R 336.1224, R 336.1225, R 336.1702(a), R 336.1910, R 336.1911, 40 CFR 52.21(c) and (d))**

5. The permittee shall either maintain a minimum of 0.007 inches of water pressure differential between the PTE and the adjacent area on a continuous basis or maintain a facial velocity of 200 feet per minute through each natural draft opening of the PTE on a continuous basis. **(R 336.1205, R 336.1702(a), R 336.1910)**

#### **IV. DESIGN/EQUIPMENT PARAMETER(S)**

1. The permittee shall not operate any booth of FGCENTRALPAINT unless the water curtain particulate control is installed and operating in a satisfactory manner. **(R 336.1224, R 336.1301, R 336.1910)**
2. The permittee shall equip and maintain each booth of FGCENTRALPAINT with highly efficient electrostatic paint applicators or comparable technology with equivalent transfer efficiency. **(R 336.1702(a))**
3. The permittee shall not operate EUCENTRALPAINT portion of FGCENTRALPAINT unless the RTO is installed, maintained, and operated in a satisfactory manner. Satisfactory operation of the RTO includes a minimum capture efficiency for EUCENTRALPAINT of 100 percent (by weight), a minimum VOC destruction efficiency for the RTO of 95 percent (by weight), maintaining a minimum combustion zone temperature of 1400°F, or the minimum combustion zone temperature from the most recent acceptable stack test, and a minimum retention time of 0.5 seconds. **(R 336.1205, R 336.1702(a), R 336.1910)**
4. The permittee shall install, calibrate, maintain and operate in a satisfactory manner a temperature monitoring device in the combustion chamber of the RTO to monitor and record the temperature on a continuous basis, during operation of EUCENTRALPAINT portion of FGCENTRALPAINT. **(R 336.1702(a), R 336.1910)**
5. The permittee shall not operate EUCENTRALPAINT portion of FGCENTRALPAINT unless the PTE is installed, maintained and operated in a satisfactory manner. Satisfactory operation requires the following: **(R 336.1702(a), R 336.1910)**
  - a) The direction of the air flow at all times must be into the enclosure; and either
  - b) The average facial velocity of air through all natural draft openings in the enclosure must be at least 200 feet per minute; or
  - c) The pressure drop across the enclosure must be at least 0.007 inch H<sub>2</sub>O
6. The permittee shall install, calibrate, maintain and operate, in a satisfactory manner, a device to measure the average facial velocity of air or a device to monitor the pressure differential between the PTE for EUCENTRALPAINT portion of FGCENTRALPAINT and the adjacent area on a continuous basis during operation of any portion of EUCENTRALPAINT. **(R 336.1702(a), R 336.1910)**
7. The permittee shall not operate EUSPINELLE portion of FGCENTRALPAINT unless the composite mesh pad system is installed, maintained and operated in a satisfactory manner. Satisfactory operation of the composite

mesh pad system includes but is not limited to maintaining the pressure drop across the scrubber systems per manufacturer specifications or as determined during compliance testing. **(R 336.1224, R 336.1225, R 336.1910)**

## **V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the VOC content, water content, and density of any coating as applied and as received, using federal Reference Test Method 24. Upon prior approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1702(a), R 336.1001, R 336.2003, R 336.2004, R 336.2040(5))**
2. The permittee shall verify the VOC destruction efficiency of the RTO, by testing at owner's expense, in accordance with Department requirements. The permittee must complete the test once every five years after the initial test. Testing shall be performed using an approved EPA Method listed in 40 CFR Part 60, Appendix A. An alternate method, or a modification to the approved EPA Method, may be specified in an AQD approved Test Protocol. No less than 30 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. The AQD must approve the final plan prior to testing, including any modifications to the method in the test protocol that are proposed after initial submittal. The permittee must submit a complete report of the test results to the AQD Technical Programs Unit and District Office within 60 days following the last date of the test. **(R 336.1702(a), R 336.1910, R 336.2001, R 336.2003, R 336.2004)**
3. Upon request of the District Supervisor, the permittee shall verify the enclosure meets the definition of PTE or verify capture efficiency of the enclosure, by testing at owner's expense, in accordance with Department requirements. Testing shall be performed using an approved EPA Method listed in 40 CFR Part 51, Appendix M. An alternate method, or a modification to the approved EPA Method, may be specified in an AQD approved Test Protocol. No less than 30 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. The AQD must approve the final plan prior to testing, including any modifications to the method in the test protocol that are proposed after initial submittal. The permittee must submit a complete report of the test results to the AQD Technical Programs Unit and District Office within 60 days following the last date of the test. **(R 336.1702(a), R 336.1910, R 336.2001, R 336.2003, R 336.2004)**
4. The permittee shall verify the total chromium emission rate from EUSPINELLE portion of FGCENTRALPAINT, by testing at the owner's expense, in accordance with Department requirements. The permittee must complete the test once every five years after the initial verification. Testing shall be performed using an approved EPA Method listed in 40 CFR 60, Appendix A. An alternate method, or a modification to the approved EPA Method, may be specified in an AQD approved Test Protocol. No less than 30 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. The AQD must approve the final plan prior to testing, including any modifications to the method in the test protocol that are proposed after initial submittal. The permittee must submit a complete report of the test results to the AQD Technical Programs Unit and District Office within 60 days following the last date of the test. **(R 336.1224, R 336.1225, R 336.1702, R 336.1902, R 336.2001, R 336.2003, R 336.2004)**

## **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1225, R 336.1702(a))**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material, including the weight percent of each component used within FGCENTRALPAINT. The data may consist of Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702(a))**

3. The permittee shall keep the following information on a calendar month basis for FGCENTRALPAINT:
- Gallons (with water) of each paint, coating, reducer, purge and clean-up solvent, *etc.* (material) used and reclaimed.
  - VOC content (with water) of each material as applied.
  - VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
  - VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.
  - Calculation of the weight percentage of purge solvents recovered, reclaimed, recycled or disposed of.

The permittee shall keep the records using mass balance, or an alternate method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1702(a))**

4. The permittee shall monitor and record, in a satisfactory manner, the temperature in the RTO on a continuous basis in a manner and with instrumentation acceptable to the Air Quality Division. Continuous temperature data recording shall consist of measurements made at equally spaced intervals, not to exceed 15 minutes per interval. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702(a), R 336.1910)**
5. The permittee shall monitor and record, in a satisfactory manner, the air flow or pressure differential between the PTE for EUCENTRALPAINT portion of FGCENTRALPAINT and the adjacent area, on a continuous basis, to verify that air is entering the PTE. Continuous pressure differential data recording shall consist of measurements made at equally spaced intervals, not to exceed 15 minutes per interval. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1702)**
6. The permittee shall perform inspections of the composite mesh pad (CMP) system associated with EUSPINELLE as follows at a minimum: **(R 336.1224, R 336.1225, R 336.1910)**
- Determine pressure drop across the CMP system on a daily basis. If the pressure drop across the control varies by more than  $\pm 2$  inch of water gauge, from the pressure drop determined during compliance testing, the permittee shall document the variation, and review the operation and maintenance procedures. The permittee shall document any corrective action.
  - Visually inspect the CMP system, on a quarterly basis, to ensure there is proper drainage, no chromic acid build up on the pads, and no evidence of chemical attack on the structural integrity of the control device.
  - Visually inspect the back portion of the mesh pad closest to the fan, on a quarterly basis, to ensure there is no breakthrough of chromic acid mist.
  - Visually inspect ductwork from tanks to the CMP system, on a quarterly basis, to ensure there are no leaks.
  - Perform wash-down of composite mesh pads in accordance with manufacturer's recommendations.
7. The permittee shall monitor continuously and record daily, in a satisfactory manner, the pressure drop across the composite mesh pad system for EUSPINELLE portion of FGCENTRALPAINT. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1702)**

## **VII. REPORTING**

1. The permittee shall notify the Department if a change in land use occurs for property classified as industrial or as a public roadway, where this classification was relied upon to demonstrate compliance with Rule 225(1). The permittee shall submit the notification to the AQD District Supervisor, within 30 days of the actual land use change. Within 60 days of the land use change, the permittee shall submit to the AQD District Supervisor a plan for complying with the requirements of Rule 225(1). The plan shall require compliance with Rule 225(1) no later than one year after the due date of the plan submittal. <sup>1</sup> **(R 336.1225(4))**

## **VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter / Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV-Scrubber (Scrubber)	28	57	R 336.1225, 40 CFR 52.21(c) & (d)
2. SV-RTO (Regenerative Thermal Oxidizer)	64	63	R 336.1225, 40 CFR 52.21(c) & (d)
3. SV-Oven1 (Indirect Natural Gas Fired Oven) <sup>a</sup>	12	49	R 336.1225, 40 CFR 52.21(c) & (d)
4. SV-Oven2 (Indirect Natural Gas Fired Oven) <sup>a</sup>	12	49	R 336.1225, 40 CFR 52.21(c) & (d)
5. SV-Oven3 (Indirect Natural Gas Fired Oven) <sup>a</sup>	12	49	R 336.1225, 40 CFR 52.21(c) & (d)
a. This stack is only for natural gas combustion.			

#### **IX. OTHER REQUIREMENT(S)**

1. The permittee shall comply with all applicable provisions of the National Emission Standards for Hazardous Air Pollutants, as specified in 40 CFR Part 63, Subpart A and Subpart PPPP for the surface coating of plastic parts and products by the initial compliance date. **(40 CFR Part 63, Subpart A and Subpart PPPP)**
2. The permittee shall comply with all applicable provisions of the National Emission Standards for Hazardous Air Pollutants, as specified in 40 CFR Part 63, Subpart A and Subpart DDDDD for Industrial, Commercial, and Institutional Boilers and Process Heaters by the initial compliance date. **(40 CFR Part 63, Subpart A and Subpart DDDDD)**

#### **Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).