

**MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY  
AIR QUALITY DIVISION**

October 29, 2019

**PERMIT TO INSTALL**  
113-19

**ISSUED TO**  
Proliant Dairy Michigan, LLC

**LOCATED AT**  
1660 Technical Drive  
Saint Johns, Michigan

**IN THE COUNTY OF**  
Clinton

**STATE REGISTRATION NUMBER**  
P0954

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: <b>October 12, 2019</b>	
DATE PERMIT TO INSTALL APPROVED: <b>October 29, 2019</b>	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

**PERMIT TO INSTALL**

**Table of Contents**

COMMON ACRONYMS .....	2
POLLUTANT / MEASUREMENT ABBREVIATIONS.....	3
GENERAL CONDITIONS .....	4
EMISSION UNIT SPECIAL CONDITIONS.....	6
EMISSION UNIT SUMMARY TABLE .....	6
EU-1 .....	7
EU-2 .....	10
EU-4 .....	13
EU-5 .....	15
EU-6 .....	17
EU-7 .....	19
EU-8 .....	21
EU-9 .....	23

### COMMON ACRONYMS

AQD	Air Quality Division
BACT	Best Available Control Technology
CAA	Clean Air Act
CAM	Compliance Assurance Monitoring
CEMS	Continuous Emission Monitoring System
CFR	Code of Federal Regulations
COMS	Continuous Opacity Monitoring System
Department/department/EGLE	Michigan Department of Environment, Great Lakes, and Energy
EU	Emission Unit
FG	Flexible Group
GACS	Gallons of Applied Coating Solids
GC	General Condition
GHGs	Greenhouse Gases
HVLP	High Volume Low Pressure*
ID	Identification
IRSL	Initial Risk Screening Level
ITSL	Initial Threshold Screening Level
LAER	Lowest Achievable Emission Rate
MACT	Maximum Achievable Control Technology
MAERS	Michigan Air Emissions Reporting System
MAP	Malfunction Abatement Plan
MSDS	Material Safety Data Sheet
NA	Not Applicable
NAAQS	National Ambient Air Quality Standards
NESHAP	National Emission Standard for Hazardous Air Pollutants
NSPS	New Source Performance Standards
NSR	New Source Review
PS	Performance Specification
PSD	Prevention of Significant Deterioration
PTE	Permanent Total Enclosure
PTI	Permit to Install
RACT	Reasonable Available Control Technology
ROP	Renewable Operating Permit
SC	Special Condition
SCR	Selective Catalytic Reduction
SNCR	Selective Non-Catalytic Reduction
SRN	State Registration Number
TBD	To Be Determined
TEQ	Toxicity Equivalence Quotient
USEPA/EPA	United States Environmental Protection Agency
VE	Visible Emissions

\*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig

### POLLUTANT / MEASUREMENT ABBREVIATIONS

acfm	Actual cubic feet per minute
BTU	British Thermal Unit
°C	Degrees Celsius
CO	Carbon Monoxide
CO <sub>2</sub> e	Carbon Dioxide Equivalent
dscf	Dry standard cubic foot
dscm	Dry standard cubic meter
°F	Degrees Fahrenheit
gr	Grains
HAP	Hazardous Air Pollutant
Hg	Mercury
hr	Hour
HP	Horsepower
H <sub>2</sub> S	Hydrogen Sulfide
kW	Kilowatt
lb	Pound
m	Meter
mg	Milligram
mm	Millimeter
MM	Million
MW	Megawatts
NMOC	Non-Methane Organic Compounds
NO <sub>x</sub>	Oxides of Nitrogen
ng	Nanogram
PM	Particulate Matter
PM10	Particulate Matter equal to or less than 10 microns in diameter
PM2.5	Particulate Matter equal to or less than 2.5 microns in diameter
pph	Pounds per hour
ppm	Parts per million
ppmv	Parts per million by volume
ppmw	Parts per million by weight
psia	Pounds per square inch absolute
psig	Pounds per square inch gauge
scf	Standard cubic feet
sec	Seconds
SO <sub>2</sub>	Sulfur Dioxide
TAC	Toxic Air Contaminant
Temp	Temperature
THC	Total Hydrocarbons
tpy	Tons per year
µg	Microgram
µm	Micrometer or Micron
VOC	Volatile Organic Compounds
yr	Year

## GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). **(R 336.1301)**
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). **(R 336.1370)**
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. **(R 336.2001)**

**EMISSION UNIT SPECIAL CONDITIONS**

**EMISSION UNIT SUMMARY TABLE**

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Emission Unit ID</b>	<b>Emission Unit Description (Including Process Equipment &amp; Control Device(s))</b>	<b>Installation Date / Modification Date</b>	<b>Flexible Group ID</b>
EU-1	Indirectly heated whey permeate spray dryer. Emissions are controlled by two baghouse dust collectors operating in parallel exhausting through a common stack (SV-EP-1).	TBD	NA
EU-2	External Fluid Bed Hotside Process to dry the final whey permeate product and the External Fluid Bed Cold Side Process to cool the whey permeate product. These processes will exhaust through a common baghouse dust collector.	TBD	NA
EU-3	Two CCC processes to cool the permeate after the evaporators using cold air.	TBD	NA
EU-4	22 MMBtu/hr natural gas burner to provide heat to the permeate dryer. The burner is low NOx.	TBD	NA
EU-5	Finished product storage silo. Emissions are controlled by a baghouse dust collector.	TBD	NA
EU-6	Finished product packaging into totes or bags. Emissions are controlled by a baghouse dust collector.	TBD	NA
EU-7	Cooling tower for the evaporators. Emissions are controlled by drift eliminators.	TBD	NA
EU-8	Vacuum filter receiver. Emissions are controlled by a baghouse dust collector.	TBD	NA
EU-9	Product surge hopper. Emissions are controlled by a baghouse dust collector.	TBD	NA

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

**EU-1  
 EMISSION UNIT CONDITIONS**

**DESCRIPTION**

Indirectly heated whey permeate spray dryer.

**Flexible Group ID:** NA

**POLLUTION CONTROL EQUIPMENT**

Two baghouse dust collectors operating in parallel exhausting through a common stack (SV-EP-1).

**I. EMISSION LIMIT(S)**

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. PM	0.001 gr/dscf	Hourly	EU-1	SC V.1, VI.2	R 336.1331(1)(c)
2. PM10	0.532 pph	Hourly	EU-1	SC V.1, VI.2	40 CFR 52.21 (c) & (d)
3. PM2.5	0.266 pph	Hourly	EU-1	SC V.1, VI.2	40 CFR 52.21 (c) & (d)
4. VE	5% Opacity	6-minute average	EU-1	SC VI.3	R 336.1301(1)(c)

**II. MATERIAL LIMIT(S)**

NA

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

1. The permittee shall not operate EU-1 unless a malfunction abatement plan (MAP) as described in Rule 911(2), for the baghouse, has been submitted within 180 days of commencement of operation of EU-1, and is implemented and maintained. The MAP shall, at a minimum, specify the following:
  - a) A complete preventative maintenance program including identification of the supervisory personnel responsible for overseeing the inspection, maintenance, and repair of air-cleaning devices, a description of the items or conditions that shall be inspected, the frequency of the inspections or repairs, and an identification of the major replacement parts that shall be maintained in inventory for quick replacement.
  - b) An identification of the source and air-cleaning device operating variables that shall be monitored to detect a malfunction or failure, the normal operating range of these variables, and a description of the method of monitoring or surveillance procedures.
  - c) A description of the corrective procedures or operational changes that shall be taken in the event of a malfunction or failure to achieve compliance with the applicable emission limits.

If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. **(R 336.1301, R 336.1331, R 336.1910, R 336.1911, 40 CFR 52.21(c) & (d))**

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

1. The permittee shall not operate EU-1 unless both of the baghouse dust collectors are installed, maintained, and operated in a satisfactory manner. Satisfactory operation includes maintaining the pressure drop as described in the MAP. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**

2. The permittee shall install, calibrate, maintain and operate in a satisfactory manner a device to monitor the pressure drop across each of the two baghouses on a continuous basis. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. Upon request from the AQD District Supervisor, the permittee may be required to verify the PM, PM10, and PM2.5 emissions from EU-1 by testing at owner's expense, in accordance with Department requirements. Testing shall be performed using an approved EPA Method listed in:

<b>Pollutant</b>	<b>Test Method Reference</b>
PM	40 CFR Part 60, Appendix A; Part 10 of the Michigan Air Pollution Control Rules
PM10 / PM2.5	40 CFR Part 51, Appendix M

The emission rate during testing shall be determined by the average of the acceptable test runs performed in accordance with the method requirements. An alternate method, or a modification to the approved EPA Method, may be specified in an AQD-approved Test Protocol. No less than 30 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. The AQD must approve the final plan prior to testing, including any modifications to the method in the test protocol that are proposed after initial submittal. The permittee must submit a complete report of the test results to the AQD Technical Programs Unit and District Office within 60 days following the last date of the test. **(R 336.1331, R 336.2001, R 336.2003, R 336.2004, 40 CFR 52.21(c) & (d))**

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1301, R 336.1331, 40 CFR 52.21(c) & (d))**
2. Whenever EU-1 is operating, the permittee shall record the pressure drop of each baghouse at least once per day. If the pressure drop is outside the range established in the MAP, the permittee shall take corrective action as described in the MAP and document the corrective action taken. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**
3. The permittee shall monitor the EU-1 exhaust stack to verify compliance with the opacity limit by taking visible emission readings a minimum of once per calendar week when the equipment is operating. Either a certified or non-certified reader shall take each visible emission reading during routine operating conditions. If a certified reader observes visible emissions that exceed the opacity limit or if a non-certified reader observes visible emissions, the permittee shall take corrective action as described in the MAP and document the corrective action taken. **(R 336.1301, R 336.1911)**

**VII. REPORTING**

1. Within 30 days after completion of the installation, construction, reconstruction, relocation, or modification authorized by this Permit to Install, the permittee or the authorized agent pursuant to Rule 204, shall notify the AQD District Supervisor, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, or modification is considered to occur not later than commencement of trial operation of EU-1. **(R 336.1201(7)(a))**

**VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter / Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV-EP-1	78	123	40 CFR 52.21 (c) & (d)

**IX. OTHER REQUIREMENT(S)**

NA

**Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

**EU-2  
 EMISSION UNIT CONDITIONS**

**DESCRIPTION**

External Fluid Bed Hotside Process to dry the final whey permeate product and the External Fluid Bed Cold Side Process to cool the whey permeate product.

**Flexible Group ID:** NA

**POLLUTION CONTROL EQUIPMENT**

A common baghouse dust collector.

**I. EMISSION LIMIT(S)**

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. PM	0.001 gr/dscf	Hourly	EU-2	SC V.1, VI.2	R 336.1331(1)(c)
2. PM10	0.19 pph	Hourly	EU-2	SC V.1, VI.2	40 CFR 52.21 (c) & (d)
3. PM2.5	0.095 pph	Hourly	EU-2	SC V.1, VI.2	40 CFR 52.21 (c) & (d)
4. VE	5% Opacity	6-minute average	EU-2	SC VI.3	R 336.1301(1)(c)

**II. MATERIAL LIMIT(S)**

NA

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

1. The permittee shall not operate EU-2 unless a malfunction abatement plan (MAP) as described in Rule 911(2), for the baghouse, has been submitted within 180 days of commencement of operation of EU-2, and is implemented and maintained. The MAP shall, at a minimum, specify the following:
  - a) A complete preventative maintenance program including identification of the supervisory personnel responsible for overseeing the inspection, maintenance, and repair of air-cleaning devices, a description of the items or conditions that shall be inspected, the frequency of the inspections or repairs, and an identification of the major replacement parts that shall be maintained in inventory for quick replacement.
  - b) An identification of the source and air-cleaning device operating variables that shall be monitored to detect a malfunction or failure, the normal operating range of these variables, and a description of the method of monitoring or surveillance procedures.
  - c) A description of the corrective procedures or operational changes that shall be taken in the event of a malfunction or failure to achieve compliance with the applicable emission limits.

If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. **(R 336.1301, R 336.1331, R 336.1910, R 336.1911, 40 CFR 52.21(c) & (d))**

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

1. The permittee shall not operate EU-2 unless the baghouse dust collector is installed, maintained, and operated in a satisfactory manner. Satisfactory operation includes maintaining the pressure drop as described in the MAP. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**
2. The permittee shall install, calibrate, maintain and operate in a satisfactory manner a device to monitor the pressure drop across the baghouse on a continuous basis. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. Upon request from the AQD District Supervisor, the permittee may be required to verify the PM, PM10, and PM2.5 emissions from EU-2 by testing at owner's expense, in accordance with Department requirements. Testing shall be performed using an approved EPA Method listed in:

<b>Pollutant</b>	<b>Test Method Reference</b>
PM	40 CFR Part 60, Appendix A; Part 10 of the Michigan Air Pollution Control Rules
PM10 / PM2.5	40 CFR Part 51, Appendix M

The emission rate during testing shall be determined by the average of the acceptable test runs performed in accordance with the method requirements. An alternate method, or a modification to the approved EPA Method, may be specified in an AQD-approved Test Protocol. No less than 30 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. The AQD must approve the final plan prior to testing, including any modifications to the method in the test protocol that are proposed after initial submittal. The permittee must submit a complete report of the test results to the AQD Technical Programs Unit and District Office within 60 days following the last date of the test. **(R 336.1331, R 336.2001, R 336.2003, R 336.2004, 40 CFR 52.21(c) & (d))**

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1301, R 336.1331, 40 CFR 52.21(c) & (d))**
2. Whenever EU-2 is operating, the permittee shall record the pressure drop of the baghouse at least once per day. If the pressure drop is outside the range established in the MAP, the permittee shall take corrective action as described in the MAP and document the corrective action taken. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**
3. The permittee shall monitor the EU-2 exhaust stack to verify compliance with the opacity limit by taking visible emission readings a minimum of once per calendar week when the equipment is operating. Either a certified or non-certified reader shall take each visible emission reading during routine operating conditions. If a certified reader observes visible emissions that exceed the opacity limit or if a non-certified reader observes visible emissions, the permittee shall take corrective action as described in the MAP and document the corrective action taken. **(R 336.1301, R 336.1911)**

**VII. REPORTING**

1. Within 30 days after completion of the installation, construction, reconstruction, relocation, or modification authorized by this Permit to Install, the permittee or the authorized agent pursuant to Rule 204, shall notify the AQD District Supervisor, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, or modification is considered to occur not later than commencement of trial operation of EU-2. **(R 336.1201(7)(a))**

**VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter / Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV-EP-2	46	122.8	40 CFR 52.21 (c) & (d)

**IX. OTHER REQUIREMENT(S)**

NA

**Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

**EU-4  
 EMISSION UNIT CONDITIONS**

**DESCRIPTION**

22 MMBtu/hr natural gas burner to provide heat to the permeate dryer.

**Flexible Group ID:** NA

**POLLUTION CONTROL EQUIPMENT**

The burner is low NOx.

**I. EMISSION LIMIT(S)**

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. PM10	0.16 pph	Hourly	EU-4	SC V.1	40 CFR 52.21 (c) & (d)
2. PM2.5	0.16 pph	Hourly	EU-4	SC V.1	40 CFR 52.21 (c) & (d)

**II. MATERIAL LIMIT(S)**

1. The permittee shall only burn pipeline natural gas in EU-4. **(R 336.1225, R 336.1702, 40 CFR 52.21(c) & (d))**

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

NA

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

1. The maximum design heat input capacity for EU-4 shall not exceed a maximum of 22 MMBTU per hour on a fuel heat input basis. **(R 336.1225, 40 CFR 52.21(c) & (d))**
2. The permittee shall install, calibrate, maintain and operate in a satisfactory manner, a device to monitor and record the natural gas usage for EU-4 on a continuous basis. **(R 336.1225, 40 CFR 52.21(c) & (d))**
3. The permittee shall not operate EU-4 unless the low NOx burner is installed and operating properly. **(R 336.1910, 40 CFR 52.21 (c) & (d))**

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. Upon request from the AQD District Supervisor, the permittee may be required to verify the PM10 and PM2.5 emissions from EU-4 by testing at owner's expense, in accordance with Department requirements. Testing shall be performed using an approved EPA Method listed in:

Pollutant	Test Method Reference
PM10 / PM2.5	40 CFR Part 51, Appendix M

The emission rate during testing shall be determined by the average of the acceptable test runs performed in accordance with the method requirements. An alternate method, or a modification to the approved EPA Method, may be specified in an AQD-approved Test Protocol. No less than 30 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. The AQD must approve the final plan prior to testing, including any modifications to the method in the test protocol that

are proposed after initial submittal. The permittee must submit a complete report of the test results to the AQD Technical Programs Unit and District Office within 60 days following the last date of the test. **(R 336.2001, R 336.2003, R 336.2004, 40 CFR 52.21(c) & (d))**

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations/records in a format acceptable to the AQD District Supervisor and make them available by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1225, R 336.1301, R 336.1331, R 336.1702, 40 CFR 52.21(c) & (d))**
2. The permittee shall monitor and record the natural gas usage rate for EU-4 on a monthly and 12-month rolling time period basis as determined at the end of each calendar month. **(R 336.1225, R 336.1702, 40 CFR 52.21(c) & (d))**

**VII. REPORTING**

1. Within 30 days after completion of the installation, construction, reconstruction, relocation, or modification authorized by this Permit to Install, the permittee or the authorized agent pursuant to Rule 204, shall notify the AQD District Supervisor, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, or modification is considered to occur not later than commencement of trial operation of EU-4. **(R 336.1201(7)(a))**

**VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter / Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV-EP-4	30	54.3	40 CFR 52.21 (c) & (d)

**IX. OTHER REQUIREMENT(S)**

NA

**Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

**EU-5  
 EMISSION UNIT CONDITIONS**

**DESCRIPTION**

Finished product storage silo.

**Flexible Group ID:** NA

**POLLUTION CONTROL EQUIPMENT**

Emissions are controlled by a baghouse dust collector.

**I. EMISSION LIMIT(S)**

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VE	5% Opacity	6-minute average	EU-5	SC VI.3	R 336.1301(1)(c)

**II. MATERIAL LIMIT(S)**

NA

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

1. The permittee shall not operate EU-5 unless a malfunction abatement plan (MAP) as described in Rule 911(2), for the baghouse, has been submitted within 180 days of commencement of operation of EU-5, and is implemented and maintained. The MAP shall, at a minimum, specify the following:
  - a) A complete preventative maintenance program including identification of the supervisory personnel responsible for overseeing the inspection, maintenance, and repair of air-cleaning devices, a description of the items or conditions that shall be inspected, the frequency of the inspections or repairs, and an identification of the major replacement parts that shall be maintained in inventory for quick replacement.
  - b) An identification of the source and air-cleaning device operating variables that shall be monitored to detect a malfunction or failure, the normal operating range of these variables, and a description of the method of monitoring or surveillance procedures.
  - c) A description of the corrective procedures or operational changes that shall be taken in the event of a malfunction or failure to achieve compliance with the applicable emission limits.

If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. **(R 336.1301, R 336.1331, R 336.1910, R 336.1911, 40 CFR 52.21(c) & (d))**

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

1. The permittee shall not operate EU-5 unless the baghouse dust collector is installed, maintained, and operated in a satisfactory manner. Satisfactory operation includes maintaining the pressure drop as described in the MAP. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**

- The permittee shall install, calibrate, maintain and operate in a satisfactory manner a device to monitor the pressure drop across the baghouse on a continuous basis. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**

#### **V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

#### **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

- The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1301, R 336.1331, 40 CFR 52.21(c) & (d))**
- Whenever EU-5 is operating, the permittee shall record the pressure drop of the baghouse at least once per day. If the pressure drop is outside the range established in the MAP, the permittee shall take corrective action as described in the MAP and document the corrective action taken. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**
- The permittee shall monitor the EU-5 exhaust stack to verify compliance with the opacity limit by taking visible emission readings a minimum of once per calendar week when the equipment is operating. Either a certified or non-certified reader shall take each visible emission reading during routine operating conditions. If a certified reader observes visible emissions that exceed the opacity limit or if a non-certified reader observes visible emissions, the permittee shall take corrective action as described in the MAP and document the corrective action taken. **(R 336.1301, R 336.1911)**

#### **VII. REPORTING**

- Within 30 days after completion of the installation, construction, reconstruction, relocation, or modification authorized by this Permit to Install, the permittee or the authorized agent pursuant to Rule 204, shall notify the AQD District Supervisor, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, or modification is considered to occur not later than commencement of trial operation of EU-5. **(R 336.1201(7)(a))**

#### **VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter / Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV-EP-5	6	98	40 CFR 52.21 (c) & (d)

#### **IX. OTHER REQUIREMENT(S)**

NA

#### **Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

**EU-6  
 EMISSION UNIT CONDITIONS**

**DESCRIPTION**

Finished product packaging into totes or bags.

**Flexible Group ID:** NA

**POLLUTION CONTROL EQUIPMENT**

Emissions are controlled by a baghouse dust collector.

**I. EMISSION LIMIT(S)**

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VE	5% Opacity	6-minute average	EU-6	SC VI.3	R 336.1301(1)(c)

**II. MATERIAL LIMIT(S)**

NA

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

1. The permittee shall not operate EU-6 unless a malfunction abatement plan (MAP) as described in Rule 911(2), for the baghouse, has been submitted within 180 days of commencement of operation of EU-6, and is implemented and maintained. The MAP shall, at a minimum, specify the following:
  - a) A complete preventative maintenance program including identification of the supervisory personnel responsible for overseeing the inspection, maintenance, and repair of air-cleaning devices, a description of the items or conditions that shall be inspected, the frequency of the inspections or repairs, and an identification of the major replacement parts that shall be maintained in inventory for quick replacement.
  - b) An identification of the source and air-cleaning device operating variables that shall be monitored to detect a malfunction or failure, the normal operating range of these variables, and a description of the method of monitoring or surveillance procedures.
  - c) A description of the corrective procedures or operational changes that shall be taken in the event of a malfunction or failure to achieve compliance with the applicable emission limits.

If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. **(R 336.1301, R 336.1331, R 336.1910, R 336.1911, 40 CFR 52.21(c) & (d))**

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

1. The permittee shall not operate EU-6 unless the baghouse dust collector is installed, maintained, and operated in a satisfactory manner. Satisfactory operation includes maintaining the pressure drop as described in the MAP. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**

2. The permittee shall install, calibrate, maintain and operate in a satisfactory manner a device to monitor the pressure drop across the baghouse on a continuous basis. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1301, R 336.1331, 40 CFR 52.21(c) & (d))**
2. Whenever EU-6 is operating, the permittee shall record the pressure drop of the baghouse at least once per day. If the pressure drop is outside the range established in the MAP, the permittee shall take corrective action as described in the MAP and document the corrective action taken. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**
3. The permittee shall monitor the EU-6 exhaust stack to verify compliance with the opacity limit by taking visible emission readings a minimum of once per calendar week when the equipment is operating. Either a certified or non-certified reader shall take each visible emission reading during routine operating conditions. If a certified reader observes visible emissions that exceed the opacity limit or if a non-certified reader observes visible emissions, the permittee shall take corrective action as described in the MAP and document the corrective action taken. **(R 336.1301, R 336.1911)**

**VII. REPORTING**

1. Within 30 days after completion of the installation, construction, reconstruction, relocation, or modification authorized by this Permit to Install, the permittee or the authorized agent pursuant to Rule 204, shall notify the AQD District Supervisor, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, or modification is considered to occur not later than commencement of trial operation of EU-6. **(R 336.1201(7)(a))**

**VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter / Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV-EP-6 <sup>a</sup>	NA	35.6	40 CFR 52.21 (c) & (d)
<sup>a</sup> This stack is not required to be discharged unobstructed vertically upwards to the ambient air.			

**IX. OTHER REQUIREMENT(S)**

NA

**Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

**EU-7**  
**EMISSION UNIT CONDITIONS**

**DESCRIPTION**

Cooling tower for the evaporators.

**Flexible Group ID:** NA

**POLLUTION CONTROL EQUIPMENT**

Emissions are controlled by drift eliminators.

**I. EMISSION LIMIT(S)**

NA

**II. MATERIAL LIMIT(S)**

NA

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

1. The permittee shall not operate EU-7 unless a malfunction abatement plan (MAP) as described in Rule 911(2), for the drift eliminators, has been submitted within 180 days of commencement of operation of EU-7, and is implemented and maintained. The MAP shall, at a minimum, specify the following:
  - a) A complete preventative maintenance program including identification of the supervisory personnel responsible for overseeing the inspection, maintenance, and repair of air-cleaning devices, a description of the items or conditions that shall be inspected, the frequency of the inspections or repairs, and an identification of the major replacement parts that shall be maintained in inventory for quick replacement.
  - b) An identification of the source and air-cleaning device operating variables that shall be monitored to detect a malfunction or failure, the normal operating range of these variables, and a description of the method of monitoring or surveillance procedures.
  - c) A description of the corrective procedures or operational changes that shall be taken in the event of a malfunction or failure to achieve compliance with the applicable emission limits.

If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. **(R 336.1301, R 336.1331, R 336.1910, R 336.1911, 40 CFR 52.21(c) & (d))**

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

1. The permittee shall not operate EU-7 unless drift eliminators with a vendor-certified maximum drift rate of 0.005 percent or less are installed, maintained, and operated in a satisfactory manner. Satisfactory operation includes maintaining EU-7 according to the MAP. **(R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

**VII. REPORTING**

1. Within 30 days after completion of the installation, construction, reconstruction, relocation, or modification authorized by this Permit to Install, the permittee or the authorized agent pursuant to Rule 204, shall notify the AQD District Supervisor, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, or modification is considered to occur not later than commencement of trial operation of EU-7. **(R 336.1201(7)(a))**

**VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter / Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV-EP-7	120	41	40 CFR 52.21 (c) & (d)

**IX. OTHER REQUIREMENT(S)**

NA

**Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

**EU-8**  
**EMISSION UNIT CONDITIONS**

**DESCRIPTION**

Vacuum filter receiver.

**Flexible Group ID:** NA

**POLLUTION CONTROL EQUIPMENT**

Emissions are controlled by a baghouse dust collector.

**I. EMISSION LIMIT(S)**

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period / Operating Scenario</b>	<b>Equipment</b>	<b>Monitoring / Testing Method</b>	<b>Underlying Applicable Requirements</b>
1. VE	5% Opacity	6-minute average	EU-8	SC VI.3	R 336.1301(1)(c)

**II. MATERIAL LIMIT(S)**

NA

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

1. The permittee shall not operate EU-8 unless a malfunction abatement plan (MAP) as described in Rule 911(2), for the baghouse, has been submitted within 180 days of commencement of operation of EU-8, and is implemented and maintained. The MAP shall, at a minimum, specify the following:
  - a) A complete preventative maintenance program including identification of the supervisory personnel responsible for overseeing the inspection, maintenance, and repair of air-cleaning devices, a description of the items or conditions that shall be inspected, the frequency of the inspections or repairs, and an identification of the major replacement parts that shall be maintained in inventory for quick replacement.
  - b) An identification of the source and air-cleaning device operating variables that shall be monitored to detect a malfunction or failure, the normal operating range of these variables, and a description of the method of monitoring or surveillance procedures.
  - c) A description of the corrective procedures or operational changes that shall be taken in the event of a malfunction or failure to achieve compliance with the applicable emission limits.

If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. (R 336.1301, R 336.1331, R 336.1910, R 336.1911, 40 CFR 52.21(c) & (d))

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

1. The permittee shall not operate EU-8 unless the baghouse dust collector is installed, maintained, and operated in a satisfactory manner. Satisfactory operation includes maintaining the pressure drop as described in the MAP. (R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))

2. The permittee shall install, calibrate, maintain and operate in a satisfactory manner a device to monitor the pressure drop across the baghouse on a continuous basis. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**

#### **V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

#### **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1301, R 336.1331, 40 CFR 52.21(c) & (d))**
2. Whenever EU-8 is operating, the permittee shall record the pressure drop of the baghouse at least once per day. If the pressure drop is outside the range established in the MAP, the permittee shall take corrective action as described in the MAP and document the corrective action taken. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**
3. The permittee shall monitor the EU-8 exhaust stack to verify compliance with the opacity limit by taking visible emission readings a minimum of once per calendar week when the equipment is operating. Either a certified or non-certified reader shall take each visible emission reading during routine operating conditions. If a certified reader observes visible emissions that exceed the opacity limit or if a non-certified reader observes visible emissions, the permittee shall take corrective action as described in the MAP and document the corrective action taken. **(R 336.1301, R 336.1911)**

#### **VII. REPORTING**

1. Within 30 days after completion of the installation, construction, reconstruction, relocation, or modification authorized by this Permit to Install, the permittee or the authorized agent pursuant to Rule 204, shall notify the AQD District Supervisor, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, or modification is considered to occur not later than commencement of trial operation of EU-8. **(R 336.1201(7)(a))**

#### **VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter / Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV-EP-8 <sup>a</sup>	NA	35.3	40 CFR 52.21 (c) & (d)
<sup>a</sup> This stack is not required to be discharged unobstructed vertically upwards to the ambient air.			

#### **IX. OTHER REQUIREMENT(S)**

NA

#### **Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

**EU-9  
 EMISSION UNIT CONDITIONS**

**DESCRIPTION**

Product surge hopper.

**Flexible Group ID:** NA

**POLLUTION CONTROL EQUIPMENT**

Emissions are controlled by a baghouse dust collector.

**I. EMISSION LIMIT(S)**

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VE	5% Opacity	6-minute average	EU-9	SC VI.3	R 336.1301(1)(c)

**II. MATERIAL LIMIT(S)**

NA

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

1. The permittee shall not operate EU-9 unless a malfunction abatement plan (MAP) as described in Rule 911(2), for the baghouse, has been submitted within 180 days of commencement of operation of EU-9, and is implemented and maintained. The MAP shall, at a minimum, specify the following:
  - a) A complete preventative maintenance program including identification of the supervisory personnel responsible for overseeing the inspection, maintenance, and repair of air-cleaning devices, a description of the items or conditions that shall be inspected, the frequency of the inspections or repairs, and an identification of the major replacement parts that shall be maintained in inventory for quick replacement.
  - b) An identification of the source and air-cleaning device operating variables that shall be monitored to detect a malfunction or failure, the normal operating range of these variables, and a description of the method of monitoring or surveillance procedures.
  - c) A description of the corrective procedures or operational changes that shall be taken in the event of a malfunction or failure to achieve compliance with the applicable emission limits.

If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. **(R 336.1301, R 336.1331, R 336.1910, R 336.1911, 40 CFR 52.21(c) & (d))**

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

1. The permittee shall not operate EU-9 unless the baghouse dust collector is installed, maintained, and operated in a satisfactory manner. Satisfactory operation includes maintaining the pressure drop as described in the MAP. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**

2. The permittee shall install, calibrate, maintain and operate in a satisfactory manner a device to monitor the pressure drop across the baghouse on a continuous basis. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1301, R 336.1331, 40 CFR 52.21(c) & (d))**
2. Whenever EU-9 is operating, the permittee shall record the pressure drop of the baghouse at least once per day. If the pressure drop is outside the range established in the MAP, the permittee shall take corrective action as described in the MAP and document the corrective action taken. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1301, R 336.1331, R 336.1910, 40 CFR 52.21(c) & (d))**
3. The permittee shall monitor the EU-9 exhaust stack to verify compliance with the opacity limit by taking visible emission readings a minimum of once per calendar week when the equipment is operating. Either a certified or non-certified reader shall take each visible emission reading during routine operating conditions. If a certified reader observes visible emissions that exceed the opacity limit or if a non-certified reader observes visible emissions, the permittee shall take corrective action as described in the MAP and document the corrective action taken. **(R 336.1301, R 336.1911)**

**VII. REPORTING**

1. Within 30 days after completion of the installation, construction, reconstruction, relocation, or modification authorized by this Permit to Install, the permittee or the authorized agent pursuant to Rule 204, shall notify the AQD District Supervisor, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, or modification is considered to occur not later than commencement of trial operation of EU-9. **(R 336.1201(7)(a))**

**VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter / Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV-EP-9 <sup>a</sup>	NA	59.6	40 CFR 52.21 (c) & (d)
<sup>a</sup> This stack is not required to be discharged unobstructed vertically upwards to the ambient air.			

**IX. OTHER REQUIREMENT(S)**

NA

**Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).