MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY AIR QUALITY DIVISION

July 1, 2024

PERMIT TO INSTALL 6-24A

ISSUED TO Heartland RV Plant 901

LOCATED AT 1200 Haines Boulevard Sturgis, Michigan 49091

IN THE COUNTY OF

Saint Joseph

STATE REGISTRATION NUMBER P1386

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:

May 23, 2024

DATE PERMIT TO INSTALL APPROVED: July 1, 2024	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

PERMIT TO INSTALL

Table of Contents

COMMON ACRONYMS	.2
POLLUTANT / MEASUREMENT ABBREVIATIONS	. 3
GENERAL CONDITIONS	.4
EMISSION UNIT SPECIAL CONDITIONS	.6
EMISSION UNIT SUMMARY TABLE	.6
EUASSEMBLY	.7

COMMON ACRONYMS

AQD BACT CAA CAM CEMS CFR COMS Department/department/EGLE EU FG GACS GC GHGS HVLP ID IRSL ITSL LAER MACT MAERS MAP MSDS NA NAAQS NESHAP NSPS NSR PS PSD PTE PTI RACT ROP SC SC SCR SNCR SRN TBD TEQ USEPA/EPA	Air Quality Division Best Available Control Technology Clean Air Act Compliance Assurance Monitoring Continuous Emission Monitoring System Code of Federal Regulations Continuous Opacity Monitoring System Michigan Department of Environment, Great Lakes, and Energy Emission Unit Flexible Group Gallons of Applied Coating Solids General Condition Greenhouse Gases High Volume Low Pressure* Identification Initial Risk Screening Level Lowest Achievable Emission Rate Maximum Achievable Control Technology Michigan Air Emissions Reporting System Malfunction Abatement Plan Material Safety Data Sheet Not Applicable National Ambient Air Quality Standards National Emission Standard for Hazardous Air Pollutants New Source Performance Standards New Source Review Performance Specification Prevention of Significant Deterioration Permanent Total Enclosure Permit to Install Reasonable Available Control Technology Renewable Operating Permit Special Condition Selective Catalytic Reduction Selective Catalytic Reduction State Registration Number To Be Determined Toxicity Equivalence Quotient United States Environmental Protection Agency
VE	Visible Emissions

POLLUTANT / MEASUREMENT ABBREVIATIONS

acfm BTU °C CO CO ₂ e dscf dscm °F gr HAP Hg hr HP H ₂ S kW lb m m mg mm MM MW NMOC NO _x ng PM PM10 PM10 PM2.5 pph PM10 PM10 PM2.5 pph ppmv ppmv ppmv ppmv psia psig scf sec SO ₂ TAC Temp THC tpy	Actual cubic feet per minute British Thermal Unit Degrees Celsius Carbon Monoxide Carbon Dioxide Equivalent Dry standard cubic foot Dry standard cubic meter Degrees Fahrenheit Grains Hazardous Air Pollutant Mercury Hour Horsepower Hydrogen Sulfide Kilowatt Pound Meter Milligram Millimeter Milligram Millimeter Million Megawatts Non-Methane Organic Compounds Oxides of Nitrogen Nanogram Particulate Matter Particulate Matter equal to or less than 10 microns in diameter Particulate Matter equal to or less than 2.5 microns in diameter Particulate Matter equal to or less than 2.5 microns in diameter Particulate Matter equal to or less than 2.5 microns in diameter Parts per million Parts per million by volume Parts per million by volume Parts per million by volume Parts per million by volume Parts per million by weight Pounds per square inch gauge Standard cubic feet Seconds Sulfur Dioxide Toxic Air Contaminant Temperature Total Hydrocarbons Tons per year Microgram
VOC yr	Volatile Organic Compounds Year

GENERAL CONDITIONS

- 1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. (R 336.1201(1))
- 2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. (R 336.1201(4))
- 3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. (R 336.1201(6)(b))
- 4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. (R 336.1201(8), Section 5510 of Act 451, PA 1994)
- 5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy. (R 336.1219)
- 6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. (R 336.1901)
- 7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). (R 336.1912)
- 8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
- 9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
- 10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

- 11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). (R 336.1301)
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.
- 12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). (**R 336.1370**)
- 13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. (R 336.2001)

EMISSION UNIT SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Including Process Equipment & Control Device(s))	Installation Date / Modification Date	Flexible Group ID
EUASSEMBLY	Recreational vehicle assembly line where caulks, adhesives and coatings are manually applied to cabinets and trim assembly.	2-15-2024 / 7-1-2024	NA

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

EUASSEMBLY EMISSION UNIT CONDITIONS

DESCRIPTION

Recreational vehicle assembly line where caulks, adhesives and coatings are manually applied to cabinets and trim assembly.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT

NA

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOC	12.6 tpy	12-month rolling time period as determined at the end of each calendar month		SC VI.2, VI.3	R 336.1225, R 336.1702(a)

II. MATERIAL LIMIT(S)

	Matarial	1 : :4	Time Period / Operating	Farriancent	Monitoring / Testing	Underlying Applicable
	Material	Limit	Scenario	Equipment	Method	Requirements
1.	General 1 Component	2.8 lb VOC/gal	Instantaneous	EUASSEMBLY	SC VI.2, VI.3	R 336.1702(d)
	Coatings applied to metal	(minus water) ^a				
	parts	as applied				
2.	General 1 Component	2.3 lb VOC/gal	Instantaneous	EUASSEMBLY	SC VI.2, VI.3	R 336.1702(a)
	Coatings applied to plastic,	(minus water) ^a				
	wood and glass parts	as applied				
3.	Plastic solvent welding	3.3 lb VOC/gal	Instantaneous	EUASSEMBLY	SC VI.2, VI.3	R 336.1702(d)
	adhesive (ABS)	(minus water) ^a				. ,
	. ,	as applied				
a T	^a The phrase "minus water" shall also include compounds which are used as organic solvents and which are excluded					

^a The phrase "minus water" shall also include compounds which are used as organic solvents and which are exclude from the definition of volatile organic compound.

III. PROCESS/OPERATIONAL RESTRICTION(S)

- 1. The permittee shall capture all purge/clean-up solvents and waste coatings and shall store them in closed containers. The permittee shall dispose of all waste materials in an acceptable manner in compliance with all applicable state rules and federal regulations. (R 336.1224, R 336.1702(a))
- 2. The permittee shall handle all VOC and / or HAP containing materials, including coatings and solvents, in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. (R 336.1224, R 336.1225, R 336.1702(a))

IV. DESIGN/EQUIPMENT PARAMETER(S)

1. The permittee shall equip and maintain EUASSEMBLY with manual applicators and handheld spray canisters for the application of coating and cleaners. (R 336.1702(a))

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

 The permittee shall determine the VOC content, water content and density of any material, as applied and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. (R 336.1225, R 336.1702)

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

- 1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. (R 336.1224, R 336.1225, R 336.1702)
- The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. (R 336.1225, R 336.1702)
- 3. The permittee shall keep the following information on a monthly basis for EUASSEMBLY:
 - a) Gallons (with water) of each material used.
 - b) VOC content (minus water and with water) of each VOC containing material used, as applied.
 - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
 - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. (R 336.1225, R 336.1702(a) & (d)).

VII. <u>REPORTING</u>

NA

VIII. STACK/VENT RESTRICTION(S)

NA

IX. OTHER REQUIREMENT(S)

NA

Footnotes:

¹ This condition is state only enforceable and was established pursuant to Rule 201(1)(b).